



Flat



Drill-Tec™ 3" (76 mm)  
Ribbed Galvalume® Plate (Flat)



Drill-Tec™ 3" (76 mm)  
Plastic Locking Plate

Recessed



Drill-Tec™ 3" (76 mm)  
Steel Plate



Drill-Tec™ 3" (76 mm)  
Standard Steel Plate



Drill-Tec™ 3" (76 mm)  
AccuTrac® Flat Plate



Drill-Tec™ 3" (76 mm)  
AccuTrac® Recessed Plate

## Description:

Drill-Tec™ insulation plates are made of Galvalume®-coated steel for excellent corrosion protection. Also available in a 3" Plastic Locking Plate made of durable polypropylene to be used with the Drill-Tec™ #12 or Drill-Tec™ #14 fasteners. The plates meet the requirements of ASTM D6294, FM Approval Standard 4470, and DIN 50018. They are ideal for attaching both insulation and cover boards.

**Round Plates:** The round design distributes loads evenly, eliminates sharp corners that can damage the insulation or cover board, and are available in a flat profile, which is ideal for cover boards, as well as recessed profile. These plates are designed to be used with appropriate Drill-Tec™ fasteners, depending on the substrate type. For details on fasteners and substrates

please see the GAF attachment tables for TPO and PVC.

**Square Plates:** AccuTrac® Plates are designed to be used in the AccuTrac® Stand Up Tool, offering an ergonomic fastening solution for attaching insulation and cover boards. They are available in two designs, recessed and flat. Please refer to GAF-published application instructions for approved substrates and additional information requirements at [gaf.com](http://gaf.com).

For applications not listed or for additional information, contact GAF at 877-423-7663 or [designservices@gaf.com](mailto:designservices@gaf.com).

Galvalume® is a registered trademark of BIEC International Inc. and some of its licensed producers.

AccuTrac® is a registered trademark of OMG.

## Codes and Standards:

- FM Approved per Approval Standard 4470. Refer to [RoofNav.com](http://RoofNav.com) for specific assemblies.



State of Florida Approved



GAF Attachment Tables for TPO and PVC

## Product Data

Plate	Drill-Tec™ 3" (76 mm) Standard Steel Plate	Drill-Tec™ 3" (76 mm) Steel Plate	Drill-Tec™ 3" (76 mm) Ribbed Galvalume® Plate (Flat)	Drill-Tec™ 3" (76 mm) AccuTrac® Flat Plate	Drill-Tec™ 3" (76 mm) AccuTrac® Recessed Plate	Drill-Tec™ 3" (76 mm) Plastic Locking Plate
Plate Profile						
Material/ Coating	AZ-55 Galvalume®					Polypropylene
Dimensions (Diam./Width)	3" (76 mm)					
Packaging	500 per box	1,000 per bucket	1,000 per bucket	1,000 per bucket	1,000 per bucket	1,000 per box
Weight	37 lb. (16.7 kg)	37 lb. (16.7 kg)	37 lb. (16.7 kg)	43 lb. (19.5 kg)	43 lb. (19.5 kg)	25 lb. (11.34 kg)
FM Approved	✓	✓	✓	✓	✓	✓
Miami-Dade County Product Control Approved	✓	✓	✓	✓	✓	✓
State of Florida Approved	✓	✓	✓	✓	✓	✓



Visit [gaf.com](http://gaf.com)

For additional information, contact GAF Design Services at 1-877-423-7663 or [designservices@gaf.com](mailto:designservices@gaf.com)

We protect what matters most™

