





Drill-Tec™ 3" (76 mm) Plastic Locking Plate



Drill-Tec™ 3" (76 mm) AccuTrac® Flat Plate





Drill-Tec™ 3" (76 mm) Steel Plate



Drill-Tec™ 3" (76 mm) Standard Steel Plate



Drill-Tec™ 3" (76 mm) AccuTrac® Recessed Plate

Description:

Drill-Tec™ insulation plates are made of Galvalume®-coated steel for excellent corrosion protection. Also available in a 3" Plastic Locking Plate made of durable polypropylene to be used with the Drill-Tec™ #12 or Drill-Tec™ #14 fasteners. The plates meet the requirements of ASTM D6294, FM Approval Standard 4470, and DIN 50018. They are ideal for attaching both insulation and cover boards.

Round Plates: The round design distributes loads evenly, eliminates sharp corners that can damage the insulation or cover board, and are available in a flat profile, which is ideal for cover boards, as well as recessed profile. These plates are designed to be used with appropriate Drill-Tec™ fasteners, depending on the substrate type. For details on fasteners and substrates

please see the GAF attachment tables for TPO and PVC.

Square Plates: AccuTrac® Plates are designed to be used in the AccuTrac® Stand Up Tool, offering an ergonomic fastening solution for attaching insulation and cover boards. They are available in two designs, recessed and flat. Please refer to GAF-published application instructions for approved substrates and additional information requirements at gaf.com.

For applications not listed or for additional information, contact GAF at 877-423-7663 or designservices@gaf.com.

Galvalume® is a registered trademark of BIEC International Inc. and some of its licensed producers.

AccuTrac® is a registered trademarks of OMG.

Codes and Standards:

 FM Approved per Approval Standard 4470.
Refer to RoofNav.com for specific assemblies.





State of Florida Approved



GAF Attachment Tables for TPO and PVC

Product Data						
Plate	Drill-Tec™ 3" (76 mm) Standard Steel Plate	Drill-Tec™ 3" (76 mm) Steel Plate	Drill-Tec™ 3" (76 mm) Ribbed Galvalume® Plate (Flat)	Drill-Tec™ 3" (76 mm) AccuTrac® Flat Plate	Drill-Tec™ 3" (76 mm) AccuTrac® Recessed Plate	Drill-Tec™ 3" (76 mm) Plastic Locking Plate
Plate Profile		~~~	~~~	~~~~~	~~~~	
Material/ Coating	AZ-55 Galvalume®					Polypropylene
Dimensions (Diam./Width)	3" (76 mm)					
Packaging	1,000 per box	1,000 per bucket	1,000 per bucket	1,000 per bucket	1,000 per bucket	1,000 per box
Weight	37 lb. (16.7 kg)	37 lb. (16.7 kg)	37 lb. (16.7 kg)	43 lb. (19.5 kg)	43 lb. (19.5 kg)	25 lb. (11.34 kg)
FM Approved	✓	✓	✓	/	1	✓
Miami-Dade County Product Control Approved	/	/	/	/	✓	✓
State of Florida Approved	✓	✓	✓	✓	✓	✓



Visit gaf.com

