



DRILL-TEC™

Termination Bars

Description

Drill-Tec™ Termination Bars are designed to terminate single-ply membranes at parapet walls and other penetrations. They are made of extruded aluminum with a mill finish or Series #304 stainless steel alloy with pre-punched holes spaced at 6" (152.4 mm) intervals on 10' (3.05 m) long bars, and are secured using Drill-Tec™ #14 Fasteners or Drill-Tec™ Masonry Anchors.

Products and Packaging



Drill-Tec™ Flat Termination Bar – #453D

Material: 6063-T6 Extruded Aluminum

Dimensions: .09" (2.28 mm) thick x 1" (25.4 mm) wide x 10' (3.05 m) length per bar

Holes: 1/4" (6.35 mm) x 3/8" (9.53 mm) pre-punched holes on 6" (152.4 mm) o.c.

Packaging: 50 bars x 10' (3.05 m) pc. per tube. 57 lb. (25.86 kg)



Drill-Tec™ Lip Termination Bar – #453B

Material: 6063-T6 Extruded Aluminum

Dimensions: .09" (2.28 mm) thick x .75" (19 mm) wide x 10' (3.05 m) length per bar

Holes: 1/4" (6.35 mm) x 3/8" (9.53 mm) pre-punched holes on 6" (152.4 mm) o.c.

Packaging: 50 bars x 10' (3.05 m) pc. per tube. 57 lb. (25.86 kg)



Drill-Tec™ Lip SE Termination Bar with Sealant Ledge – #453WE

Material: 6063-T6 Extruded Aluminum

Dimensions: .075" (1.9 mm) thick x 1" (25.4 mm) wide x 10' (3.05 m) length per bar

Holes: 1/4" (6.35 mm) x 3/8" (9.53 mm) pre-punched holes on 6" (152.4 mm) o.c.

Packaging: 50 bars x 10' (3.05 m) pc. per tube. 50 lb. (22.68 kg)