

EverGuard® TPO Low VOC
GAF Seam Cleaner



Description:

Help prepare TPO for heat-welding by cleaning exposed or contaminated seams, removing any residual soap or other cleaners, and revitalizing aged or weathered membranes.

Application:

Minimal contamination: Membrane that has been exposed overnight or for only a few days to airborne debris, foot traffic, dew, or light precipitation can usually be cleaned with a white cloth moistened with EverGuard® Low VOC TPO Seam Cleaner. Be sure to wait for the cleaner to properly dry or flash off before welding.

Dirt contamination: Membrane that is dirt-encrusted should first be cleaned with a mildly abrasive scrubbing pad and a non-abrasive, non-bleach, low-residue cleaner. After the dirt has been removed, the membrane must be cleaned with a white cloth moistened with EverGuard® Low VOC TPO Seam Cleaner. Be sure to wait for the cleaner to properly dry or flash off before welding.

Weathering: Membrane that is weathered or oxidized should first be cleaned with a mildly abrasive scrubbing pad and EverGuard® Low VOC TPO Cleaner. After the weathered or oxidized top layer is removed, the membrane must be cleaned with a white cloth moistened with EverGuard® Low VOC TPO Seam Cleaner. Be sure to wait for the cleaner to properly dry or flash off before welding. Note: The same procedure may be needed for unexposed membrane left in inventory for a year or longer.

Bag fresh: Do not use EverGuard® Low VOC TPO Seam Cleaner on recently opened or “bag fresh” material that has been exposed for less than 12 hours, unless that material has been otherwise contaminated.

Application and Storage Notes:

Apply EverGuard® Low VOC TPO Seam Cleaner where the ambient temperature is 40°F (4°C) and rising. Store in a clean and well-ventilated area where the ambient temperature is 40°F (4°C) – 90°F (32.2°C). Do not allow to freeze. The cleaner shelf life is 12 months from date of manufacture when properly stored. The VOC content is <250 grams/liter.

Specifications

Can size	1 Gallon
----------	----------

Shipping Specifications

Cans per carton	4
Weight per case	33 lb. (14.96 kg)
Cases per pallet	48

Shipping

Product SKU	7789000
-------------	---------



Visit gaf.com

For additional information, contact GAF Design Services at 1-877-423-7663 or designservices@gaf.com

We protect what matters most™

