



## Description:

- EverGuard® Low VOC TPO Bonding Adhesive is a contact-type bonding adhesive specially designed for bonding smooth-back TPO single-ply roofing membranes and flashings to various roofing substrates.
- EverGuard® Low VOC TPO Bonding Adhesive contains less than 250 grams per liter of Volatile Organic Compounds (VOCs) and has been formulated using a blend of VOC-exempt and non-exempt solvents to help comply with regulations for single-ply roofing adhesives. Always confirm compliance with codes and regulations in the applicable jurisdiction for the project before using this product.

Physical Properties	
Base	Synthetic Polymer
Solvent	VOC-compliant blend
Flash Point	-9.4°F (-23°C)
Weight/gal.	8 lb. (3.63 kg/L)
Color	Yellow
Viscosity	1,200 – 1,700 cps
Coverage	100 – 120 sq. ft./gal. (2.45 – 2.95 m <sup>2</sup> /L)
Total Solids	37.5% – 40.5%
VOC	247 grams/L
Shelf Life	1 year, unopened
Open Time	Up to 60 minutes
Dry Time	5 – 15 minutes
Application	Roller, brush, or spray
Storage	Recommended storage temperature is between 40°F – 90°F (4.4°C – 32.2°C). Storage for continued periods outside this temperature range may shorten shelf life.
Installation Temperature	40°F (4°C) and rising

## Features and Benefits:

- Low VOC (<250 g/L)
- High coverage — up to 120 sq. ft. per gal. (2.95 m<sup>2</sup>/L) of bonded membrane
- Fast-drying solvent system
- Easy application using roller or brush
- High initial tack

### Ordering Information

Packaging	5-gal. (18.9 L) pails
Weight	40 lb. (18.1 kg.) pail
Shipping	45 pails/pallet
SKU	7784

## Codes and Compliance:

- FM Approved — refer to RoofNav.com for approved assemblies.



- Classified by UL in accordance with ANSI/UL 790. Refer to UL Product iQ for actual assemblies.



- Miami-Dade County Product Control Approved



- State of Florida Approved



Visit [gaf.com](https://www.gaf.com)

For additional information, contact GAF Design Services at 1-877-423-7663 or [designservices@gaf.com](mailto:designservices@gaf.com)

We protect what matters most™

