



Quality You Can Trust...From North America's Largest Roofing Manufacturer!™

Description

EverGuard® PVC Bonding Adhesive is a contact-type bonding adhesive specially designed for bonding PVC single-ply roofing membranes and flashings to various roofing substrates.

Features and Benefits

- Low VOC < 250 g/L
- Fast-drying solvent system
- Easy application using roller or brush
- High initial tack

Physical Properties

Base: Synthetic polymer **Solvent:** Ketone, Aromatic

Hydrocarbon

Flash Point: < 0°F (< -17.8°C) Weight/Gallon: 7.8 lbs/gallon

(.93 kg/liter) **Color:** Amber

Viscosity: 1,800 - 2,400 cps **Coverage:** 60 sq. ft/gallon (1.47 sq. m/liter) or 300 sq. ft/pail

(27.8 sq. m/pail)

Total Solids: 24% +/- 1% VOC: 199.4 grams/liter
Shelf Life: 1 year, unopened
Open Time: Up to 60 minutes

Dry Time Guide:* 5 minutes at 100°F (37.8°C), 10 minutes at 75°F (23.9°C), and 20 minutes at 40°F (4.4°C)

Application: Apply with brush or roller. See application instructions for details

*Dry Time Guide: Above is only guidance. Humidity and other factors can impact the drying time.



PVC Bonding Adhesive

Ordering Information

Item Number: 856A

Packaging: 5-gallon (18.93-liter) pails **Weight:** 36 lbs (16.33 kg)/pail

Shipping: 45 pails per pallet