

EverGuard® PVC-Coated
GAF Hercules Drain



Description:

EverGuard® PVC single-ply roofing system prefashed accessories provide roofing contractors easy-to-install, factory-built details.

Application:

EverGuard® PVC prefashed accessories are designed for use with GAF EverGuard® PVC single-ply membranes. The prefashed accessories may be installed on mechanically attached, fully adhered, or self-adhered EverGuard® PVC roofing systems. Prefashed accessories are installed using conventional techniques. See published application and specifications manual for detailed instructions.

Product Information:

The one-piece spun aluminum body has a PVC-coated flange for direct hot-air welding of PVC roof membranes. The drain flange has a depressed sump area to improve flow and facilitate drainage. The PVC RetroDrain is equipped with a heavy-duty cast aluminum strainer dome for strength and durability, and incorporates U-Flow® Seal technology, which helps provide a watertight mechanical connection to PVC or cast-iron pipes. Available in 3" (76 mm), 4" (102 mm), 5" (127 mm), and 6" (152 mm) sizes.

PVC-Coated Hercules Drain

- 0.125" (3.18 mm) 11 ga. spun aluminum
- Extra-large 17½" (445 mm) PVC-coated flange
- Sump area
- Flange has welded metal clips for dome attachment
- 12" (305 mm) long drain stem designed to bypass the existing drain bowl right to the water leader
- Incorporates U-Flow® Seal technology for a secure, watertight connection when properly installed
- Simple and easy to install
- Also available with a plastic strainer dome

SPECIFICATIONS				
Drain Body	11 ga. 0.125" (3.18 mm) spun aluminum			
Flange	17½" (445 mm) diameter with sump area			
Stem	12" (305 mm) length			
SHIPPING SPECIFICATIONS	3" (76 mm)	4" (102 mm)	5" (127 mm)	6" (152 mm)
Drains per carton	1	1	1	1
Weight per carton	7.4 lb. (3.36 kg)	7.9 lb. (3.58 kg)	7.9 lb. (3.58 kg)	8.5 lb. (3.86 kg)
Cartons per pallet	TBD	TBD	TBD	TBD
PRODUCT SKUS				
3" (76 mm)	8523N			
4" (102 mm)	8523O			
5" (127 mm)	8523P			
6" (152 mm)	8523Q			



Visit gaf.com

For additional information, contact GAF Technical Support at **1-800-766-3411** or technicalquestions@gaf.com

We protect what matters most™

