


PVC Quick Spray Adhesive



Description:

EverGuard® PVC Quick Spray Adhesive is a sprayable, solvent-based contact adhesive useful for bonding smooth EverGuard® PVC and PVC KEE membranes to various substrates.

For more information on suitable substrates, refer to the *EverGuard® TPO/PVC Adhered Roofing System Overview & General Requirements Manual*.

Features and Benefits:

- Up to 7.5 squares (69.7 sq. m) of installed membrane per canister when installed in accordance with GAF application instructions (coverage rates and flash time may vary in colder temperatures)
- Faster membrane installation than traditional solvent-based bucket and roller bonding adhesive
- High initial tack

Application:

- Substrate should be dry, clean, and free from oil, grease, and other contaminants
- Spraying from 8" - 12" (203 - 305 mm) away, apply adhesive uniformly to both the substrate and the underside of the membrane
- Allow adhesive to dry to a tacky feel before bonding membrane to substrate
- For use with standard PVC, apply at an ambient temperature of 20°F (-6.67°C) and above. For use with PVC KEE or PVC XK, apply at an ambient temperature of 40°F (4.4°C) and above. The cylinders must be kept above 70°F (21°C) for the product to spray properly. Utilize power-heated blankets and hot boxes when necessary. Ensure that cylinder temperatures stay below 150°F (65.6°C).
- Apply pressure with a push broom or weighted roller to ensure complete bonding

Product Details:

- Item Numbers: **7821**
- VOC: <250 g/L
- Shelf Life: 1 year from date of manufacture
- Installation Temperature:
PVC: 20°F (6.67°C) and rising when canister is 70°F (21°C) or above
PVC KEE: 40°F (4.4°C) and rising when canister is 70°F (21°C) or above
- Gross Weight: 40.15 lb. (18.1 kg)
- Cleaner SKU: **7822**
- Hose & Gun SKUs: **7804** and **7805**

Codes & Standards:

| | |
|-------------------------------------|--|
| ▪ UL Classified ¹ | |
| ▪ FM Approved ² | |

¹ Refer to UL Online Certification Directory for actual assemblies.

² Refer to RoofNav.com for actual assemblies.

Visit [gaf.com](https://www.gaf.com)

For additional information, contact GAF Technical Support at **877-GAF-ROOF** or technicalquestions@gaf.com

We protect what matters most™

