

## EverGuard® PVC GAF QuickLay Adhesive



### Description:

EverGuard® PVC Quick-Lay Adhesive is a one-sided, wet lay-in, water-based adhesive useful for bonding smooth EverGuard® PVC membranes to various substrates.

- Suitable for roofing and flashing membranes.
- Compatible with polyiso and fiber board, insulations, and approved gypsum panels.
- Speed up installation of smooth PVC membrane by nearly 50% compared to traditional solvent-based bonding adhesives.

### Codes and Standards:

- FM Approved — refer to [roofnav.com](http://roofnav.com) for approved assemblies.
- Classified by UL in accordance with ANSI/UL 790. Refer to UL Product iQ for actual assemblies.
- State of Florida Approved
- Miami-Dade County Product Control Approved



### Application:

- Substrate surface should be dry; clean; and free from oil, grease, and other contaminants.
- Stir the adhesive thoroughly before use, either manually or by means of powered mixing equipment.
- Apply the adhesive evenly to the substrate only, avoiding puddles.
- Do not apply the adhesive where the membrane overlaps, as this will prevent proper heat welding.
- For smooth membrane: Using a standard roller, apply adhesive at 100 sq. ft. per gallon (2.45 m<sup>2</sup> per liter) to the roof substrate surface ONLY; approximately 600 sq. ft. (6 sq.) of installed membrane per pail.
- Install membrane immediately onto wet adhesive — do NOT allow adhesive to dry. Roll membrane onto the substrate surface and broom the membrane to ensure close contact between the membrane and the substrate surface.
- Not for use with EverGuard® PVC KEE or EverGuard® PVC XK membranes.

See published application and specifications manual for detailed instructions.

Specifications	
Weight per gallon	8.5 lb./g (1 kg/L)
Viscosity	10,000 cps
Solids content %	65.5 +/- 1.5
VOC	<50 g/L
Storage	Keep from freezing; store above 40°F (4.4°C)
Installation temperature	Minimum application temperature is 40°F (4.4°C) and rising



Visit [gaf.com](http://gaf.com)

For additional information, contact GAF Technical Support at **1-800-766-3411** or [technicalquestions@gaf.com](mailto:technicalquestions@gaf.com)

We protect what matters most™

