

EverGuard® PVC GAF QuickLay Adhesive



Description:

EverGuard® PVC Quick-Lay Adhesive is a one-sided, wet lay-in, water-based adhesive useful for bonding smooth EverGuard® PVC membranes to various substrates.

- Suitable for roofing and flashing membranes.
- Compatible with polyiso and fiber board, insulations, and approved gypsum panels.
- Speed up installation of smooth PVC membrane by nearly 50% compared to traditional solvent-based bonding adhesives.

Codes and Standards:

- FM Approved — refer to roofnav.com for approved assemblies.
- Classified by UL in accordance with ANSI/UL 790. Refer to UL Product iQ for actual assemblies.
- State of Florida Approved
- Miami-Dade County Product Control Approved



Application:

- Substrate surface should be dry; clean; and free from oil, grease, and other contaminants.
- Stir the adhesive thoroughly before use, either manually or by means of powered mixing equipment.
- Apply the adhesive evenly to the substrate only, avoiding puddles.
- Do not apply the adhesive where the membrane overlaps, as this will prevent proper heat welding.
- For smooth membrane: Using a standard roller, apply adhesive at 100 sq. ft. per gallon (2.45 m² per liter) to the roof substrate surface ONLY; approximately 600 sq. ft. (6 sq.) of installed membrane per pail.
- Install membrane immediately onto wet adhesive — do NOT allow adhesive to dry. Roll membrane onto the substrate surface and broom the membrane to ensure close contact between the membrane and the substrate surface.
- Not for use with EverGuard® PVC KEE or EverGuard® PVC XK membranes.

See published application and specifications manual for detailed instructions.

| Specifications | |
|--------------------------|--|
| Weight per gallon | 8.5 lb./g (1 kg/L) |
| Viscosity | 10,000 cps |
| Solids content % | 65.5 +/- 1.5 |
| VOC | <50 g/L |
| Storage | Keep from freezing; store above 40°F (4.4°C) |
| Installation temperature | Minimum application temperature is 40°F (4.4°C) and rising |



Visit gaf.com

For additional information, contact GAF Design Services at 1-877-423-7663 or designservices@gaf.com

We protect what matters most™

