



Description:

Increase efficiency when stripping-in coated metal flanges and areas that require a reinforced membrane for flashing with factory-built EverGuard® and EverGuard Extreme® TPO Utility Flashing Membrane. This single-ply roofing system accessory provides roofing contractors with an effective, easy-to-install component. GAF manufactures these and other accessories from its proven, durable EverGuard® and EverGuard Extreme® TPO single-ply reinforced membrane. GAF TPO accessories can help you reduce installation costs, risk of leaks, and callbacks, while helping you create a uniform look.

Application:

EverGuard® and EverGuard Extreme® TPO 45-Mil and 60-Mil Utility Flashing Membrane can be installed on EverGuard® and EverGuard Extreme® TPO (any thickness) mechanically attached or fully adhered roofing systems. See published application and specifications manual for detailed instructions.

Product Information:

EverGuard® and EverGuard Extreme® 45-Mil and 60-Mil Utility Flashing Membrane is available in white.

Specifications	
8" x 100' (203 mm x 30.5 m) rolls	
Reinforced TPO membra	ine
18 lb. / 8.2 kg (45-mil), 22 lb. / 10 kg (60-mil)	
EverGuard® TPO	EverGuard Extreme® TPO
7608920	7608776
7614920	_
	Reinforced TPO membra 18 lb. / 8.2 kg (45-mil), 2 EverGuard® TPO 7608920



Visit **gaf.com**

