EverGuard® TPO-Coated SpeedTite Drain



Description:

EverGuard® TPO-Coated SpeedTite™ Roof Drains are part of the range of GAF single-ply roofing system accessories that provide contractors with easy-to-install, factory-built details.

- Reduce installed costs by up to 25% compared to field-fabricated accessories
- Factory-built accessories reduce risk of leaks and callbacks
- Uniform gesthetic look

Application:

These drains are designed for use with GAF EverGuard® and EverGuard® Extreme TPO single-ply membranes. They can be installed using conventional techniques on mechanically attached, fully adhered EverGuard® and EverGuard® Extreme TPO roofing systems. See published application and specifications manual for detailed instructions.

Specifications	
11 ga. 0.125" (3.18 mm) spun aluminum	
17.5" (445 mm) diameter with sump area	
10" (254 mm) length	
3" (76 mm) compatible	4" (102 mm) compatible
1	1
8.5 lb. / 3.86 kg	8.9 lb. / 4.04 kg
20	20
Product SKUs	
8523R	8523S
	17.5" (445 mm) diameter wi 10" (254 mm) length 3" (76 mm) compatible 1 8.5 lb. / 3.86 kg 20

Product Information:

Mechanical seal and drop-inready packaging help make the EverGuard® TPO-Coated SpeedTite™ Roof Drain one of the fastest installed drains on the market. It offers builtin vortex breaker technology for improved flow performance.

- GAF SpeedTite[™] mechanical seal (patent pending) can be made watertight in seconds without using any tools
- Installs in half the time of other insert drains, enhancing productivity
- Hand-tightened seal activator creates a symmetrical watertight connection
- One-piece seamless body provides strength and durability
- Extra-large flange allows positive attachment of roof flashing membrane
- Heavy-duty cast aluminum strainer dome and clamping ring
- Exceeds ANSI/SPRI RD1 for back flow prevention for improved flow performance
- TPO-coated flange for hot-air weld flashing



Visit gaf.com



2023 GAF • COMEG847-PDF-0123