



Description:

EverGuard® TPO Primer and EverGuard® TPO Low VOC Primer are vital to surface preparation. Rely on GAF EverGuard® Primer and Low VOC Primer to help prepare metal and membrane for application of self-adhered accessories and to help prepare membrane and pourable sealer pocket to apply EverGuard One-Part Pourable Sealant.

Temperature:

Apply the primer at an ambient air temperature of 40° F (4° C) and rising.

Application:

Cover Tape

When installing cover tape, apply the primer with a 3" roller to both the metal and membrane. Allow the primer to flash off before applying the tape.

HW Cover Tape

When installing heat weld cover tape, apply the primer with a 3" roller to the metal only. Allow the primer to flash off before applying heat weld cover tape.

Self Adhered Vent Boot

When installing the Self Adhered Vent Boot, mark the area that will be covered by the adhesive ring on the TPO. Apply the primer with a 3" roller including applying additional primer just beyond the area the ring will cover. Allow the primer to flash off before applying the Self Adhered Vent Boot

Pourable Sealant Pocket

Prior to filling the TPO Pourable Sealant Pocket, you must prime all areas that the one-part pourable sealant will come in contact with.

Codes and Compliance:

- Miami-Dade County Product Control Approved



Storage and Handling:

When not in use, ensure covers are securely in place. Store primers in a clean, well-ventilated space at 40°F (4°C) – 90°F (32.2°C). Improper sealing or storage for continued periods outside of this temperature range may shorten shelf life.

Shelf Life:

Primer shelf life is 12 months (18 months for Low VOC) from date of manufacture if unopened and properly stored.

| SPECIFICATIONS | TPO Primer | Low VOC TPO Primer* |
|-----------------|--|--|
| Can size | 1 gallon | 1 gallon |
| Cans per carton | 6 | 6 |
| Coverage Rates | 200 – 250 sq. ft. per gallon (18.6 – 23.2 m ² per liter) | 200 – 225 sq. ft. per gallon (18.6 – 20.9 m ² per liter) |
| Product SKUs | 755B | 755D |

* Maximum VOC <250g/L



Visit gaf.com

For additional information, contact GAF Design Services at 1-877-423-7663 or designservices@gaf.com

We protect what matters most™

