



# Premium Fabric – Data Sheet

## PRODUCT DESCRIPTION

GAF Premium Fabric is a tough, non-woven, stitch bonded polyester fabric that is designed for use as a reinforcing material in GAF coatings or BarrierGuard® systems.

## Physical Properties<sup>1</sup>

Weight	3.0 ounces/yd <sup>2</sup> 72 grams/m <sup>2</sup>
Tensile Strength	MD: 70 lbs (56 kg) CD: 70 lbs (35 kg) [ASTM D5034]
Elongation	MD: 25% CD: 104% [ASTM D5034]
Ball Burst	114 lbs (49 kg) [ASTM D3787]
Trapezoidal Tear	MD: 27 lbs (7.7 kg) CD: 19 lbs (9.1 kg) [ASTM D3787]
Thickness	18 mils [ASTM D1777]

<sup>1</sup> Values are approximate and subject to normal manufacturing variations. These values are not guaranteed and are provided solely as a guide.

## APPLICATION

### INSTRUCTIONS

See instructions for the specific fabric-reinforced system being installed in the *Liquid-Applied Roofing Manual* at [gaf.com](http://gaf.com).

### WARRANTY

Refer to applicable warranties and guarantees, available at [gaf.com](http://gaf.com), for complete coverage and restrictions.

### PACKAGING SIZES

300 ft long rolls, with the following widths: 4", 6", 8", 12", 16", 20", 24".

336 ft long rolls, with the following widths: 40".

### STORAGE

PRODUCT STORAGE TEMPERATURE:  
50°F – 90°F (10°C – 32°C)

Keep **GAF Premium Fabric** in a clean, dry location.

## SAFETY & HANDLING

For specific information regarding safe handling of this material, please refer to the Safety Data Sheet (SDS).

## APPROVALS

State of Florida Approved	FL620 and FL20663
Miami-Dade Approved	NOA 20-0105.10

For application questions, contact GAF Technical Support Services at **1-877-GAF-ROOF**

We protect what matters most™

