



# RepairPro Sealant – Data Sheet

## PRODUCT DESCRIPTION

RepairPro Sealant is a solvent-based synthetic, self-leveling, elastomeric sealant that can be applied to many low-slope roof surfaces. It is durable and ideal for use on emergency repairs and maintenance applications.

## APPROVED SUBSTRATES

RepairPro Sealant can be used on metal, structural concrete, copper, SBS, APP, EPDM, BUR, PVC, and TPO. It can also be used with GAF Premium Fabric on penetrations, curbs, and seams. Do not use over silicone substrates.

## PACKAGING SIZES

10 oz. (0.3 liter) tube  
1-gallon (3.8 liter) bucket

## STORAGE & SHELF LIFE

PRODUCT STORAGE TEMPERATURE:  
50°F – 90°F (10°C – 32°C) Do NOT allow sealant to freeze.

SHELF LIFE: 24 months from date of manufacture in unopened containers, if stored properly.

## APPLICATION

### INSTRUCTIONS

SUBSTRATE PREPARATION: All surfaces to be sealed must be clean and free from oil, grease, and any foreign matter. Excess water should be removed, if possible, before application.

MIXING: Do NOT attempt to thin or self-tint.

APPLICATION: RepairPro Sealant may be applied by brush, or trowel. Apply to repair areas at a minimum wet thickness of 1/8" and spread at least 3" in all directions from the affected area.

## WARRANTY

See GAF RepairPro Sealant 1-Year Limited Warranty at [gaf.com](http://gaf.com) for complete coverage and restrictions.

## LIMITATIONS & PRECAUTIONS

APPLICATION AIR TEMPERATURE: Min. 40°F (5°C). Do NOT heat containers.

APPLICATION SURFACE TEMPERATURE:  
40°F – 110°F (5°C – 43°C). Cool temperatures/high humidity may slow curing.

## SAFETY & HANDLING

For specific information regarding safe handling of this material, please refer to the Safety Data Sheet (SDS).

## CLEAN UP

Use mineral spirits or xylene to thoroughly flush equipment.

## Physical Properties<sup>1</sup>

Solids by Weight	77% [ASTM D1644]
Solids by Volume	66% [ASTM D2697]
Weight per Gallon/Liters	10.3 lb. (1.23 kg) [ASTM D1475]
VOC	<300 g/L
Tensile Strength	485 psi (3344 kPa) [ASTM D412]
Elongation	300% [ASTM D412]
Flash Point	103°F (39°C)
Standard Colors	Black and White

<sup>1</sup> Values are approximate and subject to normal manufacturing variations. These values are not guaranteed and are provided solely as a guide.

## APPROVALS

State of Florida Approved - FL620

For application questions, contact GAF Technical Support Services at **1-877-GAF-ROOF**

We protect what matters most™

