

# BUR Mineral Surfaced Cap Sheet



## GAFGLAS® GAF Mineral Surfaced Cap Sheet



ITEM CODES:  
1 SQ ROLL - 3403  
1.25 SQ ROLL - 3404

### Description:

GAFGLAS® Mineral Surfaced Cap Sheet is an asphalt-coated glass fiber mat cap sheet surfaced with mineral granules.

### Uses:

GAFGLAS® Mineral Surfaced Cap Sheet is used as the surfacing ply in the application of hot-applied built-up roofs and as a top ply in base flashing construction.

### Advantages:

- Durability — glass base helps resist the effects of moisture on the roof system.
- Protection — granule surface protects against ultraviolet damage.
- Aesthetic — attractive granule surface requires no additional coating.
- Product warranties and system guarantees are available. Contact your local sales representative for requirements, availability, and limitations. See warranties and guarantees on [gaf.com](http://gaf.com) for complete coverage and restrictions.

### Product Application:



### Storage and Handling:

To prevent damage, support rolls on end in an upright position and store in a clean, dry location, covering as necessary to protect from environmental damage. Monitor environmental conditions during storage, handling, and application.

### Testing and Approvals:

- Classified by UL in accordance with ANSI/UL 790, including as component of Class A fire resistance-rated roofing assemblies. Refer to UL Product iQ for specific assemblies.
- FM Approved — refer to [roofnav.com](http://roofnav.com) for approved assemblies.
- Miami-Dade County Product Control Approved.
- State of Florida Approved.
- Texas Department of Insurance Report RC-49.
- Meets or exceeds ASTM D3909.
- For additional information, contact GAF Design Services at 1-877-423-7663 or [designservices@gaf.com](mailto:designservices@gaf.com).



### Product Specifications:

#### ASTM D3909

Roll Size* — 1 SQ	106.6 ft. <sup>2</sup> (10.0 m <sup>2</sup> )
Roll Size* — 1.25 SQ	132.9 (12.3 m <sup>2</sup> )
Roll Length — 1 SQ	32' 6" (10.0 m)
Roll Length — 1.25 SQ	40' 6" (12.3 m)
Roll Width (in)	39.375" (1.0 m)
Roll Weight — 1 SQ	68 lb. (30.4 kg)
Roll Weight — 1.25 SQ	87.5 (39.7 kg)
Roll Thickness — 1 SQ	105 mils
Roll Thickness — 1.25 SQ	95 mils
Rolls Per Pallet — 1 SQ	30
Rolls Per Pallet — 1.25 SQ	30
Full Pallet Weight — 1 SQ	2,090 lb. (948 kg)
Full Pallet Weight — 1.25 SQ	2,675 lb. (1,213 kg)
Reinforcement	Glass-Fiber

\* Roll size as reported represents actual membrane dimensions and does not calculate installation using side and end lap recommendations.

### Physical Properties:

Property	Standard Minimum Value	GAF Value
Average mass per roll, min. lb. (kg) 3" (75-mm) selvage	39.0 (31.3)	40.6 (32.5)
Mass per unit area of granule-surfaced sheet, min. lb./100 ft. <sup>2</sup> (g/m <sup>2</sup> )	63.2 (3,085)	65.1 (3,207)
MD Breaking Strength, lbf/in. (kN/m) (ASTM D5147)	8.8 (50.0)	10.8 (95.9)
XMD/CD Breaking Strength, lbf/in. (kN/m)	7.7 (44.0)	7.9 (70.5)
Mass per unit area of desaturated glass felt, min. lb./100 ft. <sup>2</sup> (g/m <sup>2</sup> )	1.70 (83)	1.75 (85)
Granule Embedment, max loss (g)	2.00	1.16
Moisture at time of manufacture (%)	1.0	≤ 1.0
Mass per unit area of mineral matter passing a 3.35 mm (No. 6) sieve and retained on a 212 μm (No. 70) sieve, min. (lb./100 ft. <sup>2</sup> ) (g/m <sup>2</sup> )	24 (1,170)	25 (1,221)
Tear Resistance lbf (N)	55 (244)	61 (271)

Note: Values stated are average values and subject to normal manufacturing variation. These values are not guaranteed and are provided solely as a guide.



Visit [gaf.com](http://gaf.com)

We protect what matters most™

