

LIBERTY™ Asphalt Primer

An easily applied foundation coating that promotes adhesion and a tough durable bond.



- Versatile use with GAF LIBERTY™ and other asphaltic roof systems
- Designed for an easy application using a roller, brush or sprayer

LIBERTY™ Asphalt Primer



Description:

LIBERTY™ Asphalt Primer is a general purpose foundation coating for all types of asphalt-based roofing materials, such as LIBERTY™ SBS Self-Adhering Base/Ply Sheet & Cap Sheet, hot-mopped or cold-applied asphalt coatings, roof cements, and asphalt-based roof and flooring adhesives.

Advantages:

- **Essential component** of the LIBERTY™ SBS Self-Adhering Roofing System
- **Provides an excellent penetration rate** while promoting a tough, durable bond for coating and adhesives
- **Strength and flexibility** accommodates temperature-related expansion and contraction of the roof system
- **Easy application** method including a roller, brush, or sprayer; maintains excellent low-temperature flexibility

Uses:

LIBERTY™ Asphalt Primer has an excellent penetration rate that promotes a tough foundation coating for:

- Concrete and masonry roofs, walls, or floors prior to the use of asphalt cutback adhesives
- Metal edging and flashing, asphalt, or weathered composition roofing prior to the application of hot-mopped or cold-applied built-up roofing materials

Surface Preparation:

All surfaces to be primed must be clean, dry, and free from any foreign matter. Sweep (or wire brush metal surfaces) and remove oil, grease, dirt, or debris that could inhibit bonding capabilities.

Application:

Material Preparation: Stir well before application.

Application Rate: Typical application rate is ½ gallon per square (0.2 L/m²); varies with texture of surface to be primed. Drying time is 4–8 hours between coats.

Application Method: Apply primer with a roller, brush, or sprayer, covering the surface at an even 1 gallon per 500 square feet (0.08 L/m²).

Temperature Range: Apply only when temperatures are 45°F (7.2°C) and rising. Cold weather will cause product to stiffen, making application difficult. Store 24 hours at room temperature prior to application. Do not heat container or attempt to thin this product. Not recommended for application on substrates that exceed 140°F (60°C).

Precautions

Observe normal safeguards for storing and handling of this product prior to and during application. Use with adequate ventilation. Wear protective clothing, including chemical-resistant gloves and protective goggles.

Code Approvals:

LIBERTY™ Asphalt Primer is listed and approved by the following agencies or code bodies: Meets or exceeds the requirements of ASTM D41 Type 1 Asphalt Primer Used in Roofing, Damp Roofing, and Waterproofing. Approvals may vary by region. Be sure to review pail labels before purchase.

- **State of Florida Approved**

- **Miami-Dade County Product Control Approved***



- **Meets or exceeds ASTM D41 Type 1**

* Formerly known as Matrix 307 Premium Asphalt Primer
Note: Approvals may vary by region. Be sure to review pail labels before purchase.

Product Specifications (Nominal):

Weight	7.4 lb. (3.36 kg)/gal
VOC (max)	350 g/L
Non-volatile Content	85% by weight minimum
Sizes	1 gallon (3.79 L)



For further information on this product, see Safety Data Sheet at gaf.com. For questions on application, contact GAF at **877-GAF ROOF** or visit gaf.com

We protect what matters most™

