



LIBERTY™ SBS Self-Adhering Roofing System

Help protect your low-slope roof and use no special tools when installing a granule-surfaced self-adhering roofing system



- Provides durable protection for the low-slope areas of your property
- Installs quickly and easily without the hassles of bulky equipment or unpleasant odor
- Applied without torches, open flames, or hot asphalt

LIBERTY™ SBS Self-Adhering Roofing System



Porches



Carports



Garages



Sheds

Benefits:

- **Self-adhering base/ply sheet and cap sheet** provide convenient peel and stick installation, eliminating open flames on your roof
- **No torches, kettles, or dangerous chemicals**
- **No fumes or odors** caused by hot asphalt
- **Seven popular colors** to complement your Timberline® or other GAF asphalt shingle roof (see below)
- **Minimal set-up and clean-up time** can speed up installation as compared with mopped SBS systems
- **No need to stage expensive equipment**
- **Utilizes similar technology** to GAF RUBEROID® SBS-modified bitumen membranes
- **Versatile installation options** available. Perfect for primed low-slope roof areas ¼:12 – 3:12.

- **Up to 20-Year Limited Warranty** covering manufacturing defects, available for select systems*
- **System guarantees covering material defects and workmanship errors are also available for purchase** for approved systems installed by GAF certified contractors. Contact GAF for specific requirements.†

Accessory Benefits:

- **Both Flashing Cement and Asphalt Primer** are components for GAF LIBERTY™ and other SBS-modified asphalt roofing systems
- **Flashing Cement** offers excellent bonding strength and high flexibility to accommodate temperature-related expansion and contraction of the roof system
- **Asphalt Primer** promotes a tough, durable bond for asphaltic systems

System Details:

Specifications (approximate)‡

- **LIBERTY™ Self-Adhering Base/Ply Sheet**
 - Roll size: 2 squares§ (216 sq. ft. [20.1 m²]) — excludes laps
 - Roll width: 39.375" (1.0 m)
 - Roll length: 66' (20.1 m)
 - Approx. roll weight: 82 lb. (37.2 kg)
 - Roll thickness: 0.068" (1.73 m)
- **LIBERTY™ Self-Adhering Cap Sheet**
 - Roll size: 1 square§ (112 sq. ft. [10.4 m²]) — excludes laps
 - Roll width: 39.375" (1.0 m)
 - Roll length: 34' (10.4 m)
 - Approx. roll weight: 96.4 lb. (43.7 kg)
 - Roll thickness: 0.157" (4.0 m)
- **LIBERTY™ Asphalt Primer**
 - Size: 1 gallon (3.79 L)
 - Weight: 7.4 lb. (3.36 kg)/gal
 - VOC (max): 350 g/L
 - Non-volatile content: 85% by weight minimum
- **LIBERTY™ Flashing Cement**
 - Size: 1 gallon (3.79 L)
 - Weight: 9.1 lb. (4.1 kg)/gal
 - VOC (max): <250 g/L
 - Non-volatile content: 65% minimum SETA
 - Flash point: 110°F (43.3°C)

Codes & Standards:

■ UL Listed to ANSI/UL790** ***	
■ FM Approved††† †††	
■ Miami-Dade County Product Control approved†† §§	
■ Texas Dept. of Insurance Report RC-121	
■ State of Florida Approved	

Base/Ply Sheet:

- UL Evaluation Report UL ER1306-02
- Meets or exceeds ASTM D4601, Type II
- Meets or exceeds ASTM D1970

Cap Sheet:

- Meets or exceeds D6164, Type I, Grade G

Asphalt Primer:

- State of Florida Approved
- Meets or Exceeds ASTM D41

Flashing Cement:

- Meets or Exceeds ASTM D4586, Type 1
- Meets or Exceeds ASTM D3409

‡ Values stated are approximate and subject to normal manufacturing variation. These values are not guaranteed and are provided solely as a guide.

§ Installed coverage will be lower and depend on quantity and width of side and end laps.

*** Refer to UL Product iQ for actual assemblies.

†† Refer to FM RoofNav.com for actual assemblies.


†† Formerly known as Matrix 307 Premium Asphalt Primer.

§§ Formerly known as Matrix 201 Premium SBS Flashing Cement

*** LIBERTY™ 1-Ply System is NOT UL Classified with an ANSI/UL 790 roofing fire rating. However, the LIBERTY™ 2-Ply System is UL Classified with an ANSI/UL 790 Class C roofing fire rating.

††† Not including the LIBERTY™ Cap Sheet.

Complementary Color Options:



Black



Hickory



Shakewood



Tan



Slate



Weathered Wood




White

Note: These blended colors are designed to complement your shingles, not to be an exact match. Because of the small size of these samples, it's difficult to reproduce the actual color effect. Please be sure to see a full-size roll before making or installing a final color selection.

* Exclusions apply. See *Limited Warranty on LIBERTY™ SBS Self-Adhering Materials* for complete coverage and restrictions.

† See Low-Slope Addendum to the *System Plus Limited Warranty*, Low-Slope Addendum to the *Silver Pledge™ Limited Warranty*, and Low-Slope Addendum to the *Golden Pledge® Limited Warranty* for complete coverage and limitations.



For further information on this system, please visit **gaf.com/Liberty**. For questions on application, call **877-GAF ROOF**

We protect what matters most™

