

Specially designed to replicate the look of old asbestos siding



- Virtually identical in size and shape to many old asbestos siding shingles that are no longer available
- WeatherSide™ Fiber-Cement Siding contains NO asbestos
- Great for siding small additions, changing windows, or for making small repairs without the hassles and expense of installing new siding on the entire house




WeatherSide™ Fiber-Cement Siding

Benefits:


- **Distinct design**, unavailable in other siding products, helps to closely replicate the look of older, no-longer-available asbestos siding
- After properly removing and disposing of the old siding in accordance with local, state, and federal regulations regarding asbestos-containing products², **simply nail in place and paint**
- Unlike some other fiber-cement siding products, **no caulking is required at the joints**
- **Pre-primed from the factory** and ready to paint the color of your choice
- **Durable fiber-cement construction** helps resist warping, rotting, expansion/contraction, UV degradation, and termite damage
- **UL Classified** to ANSI/UL723
- **Non-Combustible** in accordance with ASTM E136
- Backed by a **25-year limited warranty**¹

Siding Shingle Selector:




Purity™ Shingle

Textured surface with Straight, Wavy, or Thatched edge.



Emphasis™ Shingle

Extra-thick wood grain look with Thatched edge.



Profile™ Shingle

Striated surface with Straight edge.

Approx. Specs	Purity Straight™/Wavy™	Purity Thatched™	Emphasis™	Profile™ 9	Profile™ 12	Profile™ 14
Size	12 in. x 24 in.	12 in. x 24 in.	14 5/8 in. x 25 5/32 in.	9 x 32 in.	12 x 24 in.	14 5/8 in. x 32 in.
Exposure	11 in.	10 1/2 in.	13 in.	8 in.	11 in.	13 5/8 in.
Thickness	1 1/64 in.	1 1/64 in.	9/32 in.	1 1/64 in.	1 1/64 in.	1 1/64 in.
Pcs./Bundle	18	19	11	19	18	11
Bundles/Sq.	3	3	4	3	3	3
Sq./Pallet	20	20	10	15	20	15
Lb./Sq.	168	186	268	177	165	171



Visit gaf.com/WeatherSide

Product Details:

Siding Standards & Code Approvals:

- UL Classified to ANSI/UL723
- ASTM E136 non-combustible
- Meets or exceeds ASTM C1186
- State of Florida approved
- Meets or exceeds the requirements of the Texas Department of Insurance (excludes Profile™ 14)
- Miami-Dade County Product Control Approved (excludes Emphasis™ and Profile™ 14)

Matching Accessories:

WeatherSide™ Fiber-Cement Siding accessories offer faster, easier, more accurate installation, and include:



1 3/4" Hot-Dipped Galvanized Siding Nails



Backer Strips (9", 12", and 14")



Individual Pre-Primed Corners with Woodgrain Surface (9", 12", 14", and Emphasis™)

¹ See WeatherSide™ Fiber-Cement Siding Limited Warranty for complete coverage and limitations.

² If your project involves the handling, removal, and/or disposal of asbestos-containing products, always use a licensed asbestos-abatement professional.

We protect what matters most™

