

GAF
Safety Data Sheet
SDS # 4067

SDS Date: July 2021

1. IDENTIFICATION

PRODUCT NAME: Acrylic Base Coat

MANUFACTURER: GAF

ADDRESS: 1 Campus Drive, Parsippany, NJ 07054

24-HOUR EMERGENCY

PHONE (CHEMTREC): 800 – 424 – 9300

INFORMATION ONLY: 800 – 766 – 3411

PREPARED BY: Corporate EHS

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Label elements

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Carcinogenicity Category 2
Skin Irritation Category 3
Eye Irritation Category 2B

Pictogram:



Signal word: Warning
Hazard statement(s)
Causes mild skin irritation.
Causes eye irritation.
Suspected of causing cancer.



Precautionary Statements - Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wash face, hands and any exposed skin thoroughly after handling.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves.

Wear eye or face protection.

Use only outdoors or in a well-ventilated area.

Avoid breathing vapor.

Contaminated work clothing should not be allowed out of the workplace.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.

IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Hazards not otherwise classified (HNOC)

Not applicable.

Other Information

Unknown acute toxicity.

ADDITIONAL HAZARD IDENTIFICATION INFORMATION:

SIGNS & SYMPTOMS OF EXPOSURE

EYES: Direct contact with the eyes may cause temporary irritation.

SKIN: Slight irritation of the skin. Prolonged contact can cause reddening

of the skin.

INGESTION: Expected to be a low ingestion hazard.

INHALATION: May cause irritation.

ACUTE HEALTH HAZARDS: Skin irritation.

CHRONIC HEALTH HAZARDS: None known.

CARCINOGENICITY: IARC has determined that occupational exposure to Titanium Dioxide is

possibly carcinogenic to humans (Group 2B).

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Chemical Name	CAS No.	Weight-%
Calcium Carbonate	1317-65-3	20 - 25
Alumina Trihydrate	21645-51-2	10 - 15
Titanium Dioxide	13463-67-7	5 – 10
Non-hazardous ingredients	-	60 – 65



4. FIRST AID MEASURES

Description of first aid measures

Eye contact Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids.

Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get

medical attention.

Skin contact Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash

contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly

before reuse.

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. If

necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway.

Ingestion Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at

rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Get medical

attention immediately.

Most important symptoms and effects, both acute and delayed Slight irritation of eyes and skin.

<u>Indication of any immediate medical attention and special treatment needed</u> Provide general supportive measures and treat symptomatically. Keep the victim under observation. Symptoms may be delayed.

Note to physicians Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment including water fog, dry chemical powder, carbon dioxide.

<u>Unsuitable extinguishing media</u> None known.

Specific hazards arising from the chemicalNo information available.

Explosion data In a fire or if heated, a pressure increase will occur and the container may burst.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Isolate materials not yet involved in the fire and protect personnel. Move containers from the fire area if this can be done without risk; otherwise, cool with carefully applied water spray. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate



ventilation. For personal protection see section 8.

Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Methods and material for containment and cleaning up

Methods for containmentContain spill if safe to do so. Prevent entry into drains, sewers, and other waterways. Soak

up with a non- combustible absorbent material and place in an appropriate container for disposal. Dispose of in accordance with applicable Federal, State, and local procedures (see

section 13).

Methods for cleaning up

Stop leak if without risk. Move containers from the spill area. Approach release from upwind.

Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in a container for disposal according to local regulations (see section 13 of SDS).

place in a container for disposal according to local regulations (see section 13 of SDS). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may

pose the same hazard as the spilled product.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice.

For exterior use only. Do not use indoors. Put on appropriate personal protective equipment (see section 8 of SDS). Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse

containers.

Conditions for safe storage, including any incompatibilities

Storage Conditions Store in original container protected from direct sunlight in a dry, cool and well-ventilated

area, away from incompatible materials (see section 10 of SDS) and food and drink. Store locked up. Keep the container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not

store in unlabeled containers

Incompatible materialsNone known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR1910.1000)

Calcium Carbonate (CAS 1317-65-3)

PEL 5 mg/m3 Respirable fraction.

15 mg/m3 Total dust.

Titanium Dioxide (CAS 13463-67-7)

PEL 15 mg/m3 Total dust.

US. ACGIH Threshold Limit Values

Aluminum Trihydroxide (CAS 21645-51-2)

TLV 1 mg/m3 Respirable fraction.



Titanium Dioxide (CAS 13463-67-7)

TLV 10 mg/m3 Respirable fraction.

Appropriate engineering controls

Engineering Controls

Showers

Eyewash stations Adequate ventilation

Individual protection measures, such as personal protective equipment

Eye/face protection Safety glasses or chemical goggles as appropriate to prevent eye contact.

Skin and body protectionChemical-resistant, impervious gloves complying with an approved standard should be worn

at all times. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. Personal protective equipment for the

body should be selected based on the task being performed and the risks involved

Respiratory protection If exposure limits are exceeded or irritation is experienced, a NIOSH/MSHA

approved respiratory protection should be worn.

General Hygiene Considerations Always observe good personal hygiene measures, such as washing after handling the

material and before eating, drinking, and/or smoking. Routinely wash work clothing and

protective equipment to remove contaminants.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state and color White heavy liquid

Property <u>Values</u>

pH No information available
Melting point/freezing point No information available
Poiling point / boiling range
Flash point > 100 deg C > 212 deg F
Too information available

Flammability (solid, gas) Non-Flammable

Flammability Limit in Air

Upper flammability limit:Non-FlammableLower flammability limit:Non-Flammable

Vapor pressure
Vapor density

No information available
No information available

Specific Gravity 1.3

Water solubilityNo information availableAutoignition temperatureNo information availableDecomposition temperatureNo information availableExplosive propertiesNo information availableOxidizing propertiesNo information available

VOC Content < 50 g/L Density 10.8 lbs/gal

10. STABILITY AND REACTIVITY

Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability

Stable under recommended storage conditions.



Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Extremes of temperature and contact with incompatible chemicals.

Incompatible materials

Strong oxidizing agents.

Hazardous Decomposition Products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Eye contact Direct contact with the eyes may cause temporary irritation.

Skin contact May cause slight skin irritation.

Ingestion Expected to be a low ingestion hazard.

Information on toxicological effects

Aluminum Trihydroxide (CAS 21645-51-2)

Acute Oral Test Results LD50 Rat > 5000 mg/kg

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization This product is not expected to cause skin sensitization..

Germ cell mutagenicity

Carcinogenicity

No information available.

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
Aspiration hazard
No information available.
No information available.
No information available.

Potential acute health effects

Eye contact : May cause mild eye irritation.
Inhalation : None known.
Skin contact : Causes mild skin irritation.

Ingestion: None known.

12. ECOLOGICAL INFORMATION

Ecotoxicity

100 % of the mixture consists of components(s) of unknown hazards to the aquatic environment.

Titanium Dioxide (CAS 13463-67-7)

Aquatic

EC50 Water flea (Daphnia magna) Mummichog (Fundulus heteroclitus) > 1000 mg/l, 48 hours LC50 Fish Fathead minnow (Pimephales promelas) > 1000 mg/l, 96 hours



Persistence and degradability

Not readily biodegradable

Bioaccumulation

No information available.

Other adverse effects

No known significant or critical hazards.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable local, regional, national and international

laws and regulations.

Contaminated packaging Do not reuse containers.

14. TRANSPORT INFORMATION

DOT Not regulated as dangerous goods.

IATA Not regulated as dangerous goods.

IMDG Not regulated as dangerous goods.

15. REGULATORY INFORMATION

US Federal Regulations

TSCA

This product and its components are listed on the TSCA 8(b) inventory.

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical

No

SARA 313 (TRI reporting)

Zinc Oxide

SARA Hazard Categories

Acute health hazard Yes
Chronic Health Hazard No
Fire hazard No
Sudden release of pressure hazard No
Reactive Hazard No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

No



US State Regulations

Other state regulations may apply. Check individual state requirements. The following components appear on one or more of the following state hazardous substances lists:

Chemical Name	CAS#	CA	MA	MN	NJ	PA	RI
Alumina Trihydrate	21645-51-2	No	No	No	No	No	No
Titanium Dioxide	13463-67-7	No	No	Yes	Yes	Yes	Yes
Calcium Carbonate	1317-65-3	Yes	Yes	Yes	Yes	Yes	Yes

California Proposition 65

Titanium dioxide and Diuron are California Proposition 65 listed substances.

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 1 Flammability 0 Instability 0 Physical and Chemical

Properties -

HMIS Health hazards 1 Flammability 0 Physical hazards 0 Personal protection X

ADDITIONAL COMMENTS: None.

DATE OF PREVIOUS SDS: None. New SDS.

CHANGES SINCE PREVIOUS SDS: New SDS.

This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee, expressed or implied, is made as to its accuracy, reliability, or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license of valid patents.