

GAF Safety Data Sheet SDS # 4082 SDS Date: October 2023

SECTION 1: PRODUCT AND COMPANY INFORMATION

PRODUCT NAME:	DEXcell [®] Glass Mat Roof Board DEXcell FA [™] Glass Mat Roof Board DEXcell FA VSH [™] Glass Mat Roof Board
PRODUCT FAMILY:	Roof cover boards and roof underlayment.
MANUFACTURER:	GAF
ADDRESS:	1 Campus Drive, Parsippany, NJ 07054
24-HOUR EMERGENCY PHONE (CHEMTREC):	800 - 424 - 9300
INFORMATION ONLY:	877-GAF-ROOF
APPROVED BY:	Corporate EHS

SECTION 2: HAZARDS IDENTIFICATION

As defined in the OSHA Hazard Communication Standard, 29 CFR 1910.1200, the products listed below are considered articles and do not require an SDS. In addition, articles are not included in the scope of the Globally Harmonization System (GHS). As such, the GHS labeling elements are not included on this SDS. All components listed for this product are bound within the product. When handled as intended and under normal conditions of use, there is no evidence that any of the ingredients are released in amounts that pose a significant health risk. Although these products are not subject to the OSHA Standard or GHS labeling elements, GAF would like to disclose as much health and safety information as possible to ensure that this product is handled and used properly. This SDS contains valuable information critical to the safe handling and proper use of the product. In addition, the recommendations for handling and use of these products should be included in worker training programs.

ADDITIONAL HAZARD IDENTIFICATION INFORMATION:

PRIMARY ROUTE OF EXPOSURE:	Occasional nuisance dust, Inhalation.
SIGNS & SYMPTOMS OF EXPOSURE	
EYES:	May cause mechanical irritation.
SKIN:	May cause burns, irritation, itching or dermatitis.
INGESTION:	This product is not intended to be ingested. If ingested, it may cause temporary irritation to the gastrointestinal (digestive) tract.
INHALATION:	May cause irritation to the respiratory tract.

ACUTE HEALTH HAZARDS:	Skin and eye irritation.
CHRONIC HEALTH HAZARDS:	This product contains crystalline silica (quartz) as a naturally occurring impurity in some of the raw materials.
	Studies in humans have found that exposure to respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs. Silicosis is a serious and irreversible disease; it may be progressive even after exposure has ceased; it can lead to disability and death. Human studies also have found that silicosis is a risk factor for tuberculosis, and that occupational exposure to respirable crystalline silica is associated with chronic obstructive pulmonary disease, including bronchitis and emphysema.
CARCINOGENICITY:	Occupational exposure to respirable crystalline silica is classified as a known carcinogen in humans. IARC has determined that respirable crystalline silica is carcinogenic to humans (Group 1), based on findings of sufficient evidence of carcinogenicity in both humans and experimental animals. NTP has classified respirable crystalline silica as a known human carcinogen based on sufficient evidence of carcinogenicity from studies in humans indicating a causal relationship between occupational exposure to respirable crystalline silica and increased lung cancer rates. NIOSH has determined that respirable crystalline silica is a potential occupational carcinogen.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

			OCCUPATIONAL EX	POSURE LIMITS
CHEMICAL NAME	CAS #	% (BY WT)	OSHA	ACGIH
Calcium Sulfate Dihydrate (with crystalline silica impurities)	13397-24-5	>91	15 mg/m3 (total dust) 5 mg/m3 (respirable dust)	10 mg/m3 (total dust)
Mixture-calcium, aluminum silicates, amorphous silica	65997-17-3	<4	NE	NE
Silica, Crystalline (Quartz)	14808-60-7	Trace	50 ug/m3	0.025 mg/m3

NE = Not Established

SECTION 4: FIRST AID MEASURES

FIRST AID PROCEDURES

EYES:	Hold eyelids open and wash with gentle stream of water for at least 15 minutes preferably at eyewash fountain. Seek medical attention if irritation persists.
SKIN:	Flush and wash skin with soap and water. Utilize lotions to alleviate dryness if present. Seek medical attention if irritation persists.
INHALATION:	Remove to fresh uncontaminated air. If breathing difficulty persists, seek medical attention
INGESTION:	This product is not expected to be ingested and no harmful effects are expected upon ingestion of small amounts. Larger amounts may cause abdominal discomfort or possible obstruction of the digestive tract. Seek medical attention if problems persist.
MEDICAL CONDITIONS AGGREVATED BY EXPOSURE:	Pre-existing upper respiratory and lung diseases such as, but not limited to, bronchitis, emphysema and asthma. Pre-existing skin diseases such as, but not limited to, rashes and dermatitis.

SECTION 5: FIRE FIGHTING PROCEDURES

SUITABLE EXTINGUISHING MEDIA:	Water, alcohol foam, carbon dioxide, or dry chemical.
HAZARDOUS COMBUSTION PRODUCTS:	None known. Above 1450 deg. C, material can decompose and release sulfur dioxide (SO2) and oxides of carbon.
RECOMMENDED FIRE FIGHTING PROCEDURES:	NIOSH-approved self contained breathing apparatus is recommended for smoke protection.
UNUSUAL FIRE & EXPLOSION HAZARDS:	Not applicable.

SECTION 6: ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES:	Pick up large pieces. Avoid creating dust during clean up. This product does not present an ecological hazard to the environment.
	Dispose of in accordance with applicable federal, state, and local regulations.

SECTION 7: HANDLING AND STORAGE

HANDLING AND STORAGE:	Avoid breathing dust. Minimize generation of dust. Provide appropriate exhaust ventilation at places where dust is formed. Store material in a cool, dry, ventilated area, away from excessive heat or sunlight. Store panels flat to minimize damage and warping. Do not stack panels too high when storing to minimize the risk of falling.
	minimize the lisk of failing.

OTHER PRECAUTIONS:

Avoid contact with eyes, skin and clothing. Wear recommended PPE when handling.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS / VENTILATION:	Not applicable.
RESPIRATORY PROTECTION:	Not required under normal use conditions. In circumstances where dust or fumes are generated and may exceed recognized allowable exposure levels, appropriate NIOSH approved respiratory protection is recommended.
EYE PROTECTION:	Safety glasses with side shields
SKIN PROTECTION:	Cotton or leather gloves are recommended when handling.
OTHER PROTECTIVE EQUIPMENT:	None
WORK HYGIENIC PRACTICES:	Utilize wet methods, when appropriate, to reduce generation of dust. Wash exposed skin prior to eating, drinking or smoking and at the end of each shift.
EXPOSURE GUIDELINES:	These products should be handled using methods and techniques that minimize or eliminate dust generation.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE & ODOR:	Coated gypsum b	oard with a white/gray core. No odo	r.
FLASH POINT:	Not Applicable	LOWER EXPLOSIVE LIMIT:	Not Applicable
METHOD USED:	Not Applicable	UPPER EXPLOSIVE LIMIT:	Not Applicable
EVAPORATION RATE:	Not Applicable	BOILING POINT:	Not Applicable
pH (undiluted product):	Not Applicable	MELTING POINT:	Not Applicable
SOLUBILITY IN WATER:	2.1 g/L	SPECIFIC GRAVITY:	No Data
RELATIVE DENSITY:	2.3 g/cc	PERCENT VOLATILE:	Not Applicable
VAPOR PRESSURE:	Not Applicable	MOLECULAR WEIGHT:	Not Applicable
VOC WITH WATER (LBS/GAL):	Not Applicable	WITHOUT WATER (LBS/GAL):	Not Applicable

SECTION 10: STABILITY AND REACTIVITY

THERMAL STABILITY:

STABLE X

UNSTABLE

CONDITIONS TO AVOID (STABILITY): None known.

AVOID):

INCOMPATIBILITY (MATERIAL TO

None known.

HAZARDOUS DECOMPOSITION OR BY- PRODUCTS:	None known. Above 1450 C, material can decompose and release sulfur dioxide (SO2) and oxides of carbon.
HAZARDOUS POLYMERIZATION:	Will not occur

SECTION 11: TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INGESTION

INFORMATION: Not a likely route of exposure. May result in obstruction or temporary irritation of the digestive tract.

INHALATION

Dust may irritate the respiratory system. Chronic exposure may result in lung disease. (See below)

SKIN CONTACT

May cause burns, irritation, itching or dermatitis. (See below).

EYE CONTACT

May cause mechanical irritation.

Acute exposure to airborne dust concentrations in excess of the PEL/TLV may result in coughing, dyspnea, wheezing, and a burning irritation of the nose, throat, and upper respiratory tract, along with possible impa ired pulmonary function. Chronic exposure to crystalline silica (a naturally occurring contaminant) in the respirable size has been shown to cause silicosis, a debilitating lung disease, and lung cancer. Continued and prolonged contact may result in drying of the skin. Contact with dust or glass fibers may produce itching, rash and/or redness. Repeated or prolonged exposure may result in dermatitis.

CARCINOGENICITY:

This product contains crystalline silica (quartz) as a naturally occurring impurity in some of the raw materials. The International Agency for Research on Cancer (IARC) classifies crystalline silica inhaled in the form of quartz or cristobalite from occupational sources as carcinogenic to humans, Group 1. The National Toxicology Program (NTP) classifies respirable crystalline silica as a substance which may be reasonably anticipated to be a carcinogen. OSHA does not regulate crystalline silica as a human carcinogen. Exposures to respirable crystalline silica are not expected during the recommended use of this product. Industrial hygiene monitoring to date has not identified any detectable respirable crystalline silica in dust sampling conducted utilizing recommended application procedures. However, actual levels must be determined by workplace hygiene testing

SECTION 12: ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION:	This product does not represent an ecological hazard. Gypsum is a	
	naturally occurring mineral. Biodegradation and/or bioaccumulation is	
	not applicable.	

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of in accordance with Federal, state and local regulations.

SECTION 14: TRANSPORTATION INFORMATION

DOT

Not regulated as dangerous goods.

ΙΑΤΑ

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

SECTION 15: REGULATORY INFORMATION							
U.S. FEDERAL REGULATIONS							
TSCA:	This product and its components are listed on the TSCA 8(b) inventory.						
CERCLA:	None						
SARA							
311/312 HAZARD CATEGORIES:	None						
313 REPORTABLE INGREDIENTS:	None						
CALIFORNIA PROPOSITION 65:	Silica						

Other state regulations may apply. Check individual state requirements. The following components appear on one or more of the following state hazardous substances lists:

Chemical Name	CAS #	CA	MA	MN	NJ	ΡΑ	RI
Crystalline Silica	14808-60-7	Yes	Yes	Yes	Yes	Yes	Yes

 SECTION 16: OTHER INFORMATION

 ADDITIONAL COMMENTS:
 None.

 DATE OF PREVIOUS SDS:
 None.

 CHANGES SINCE PREVIOUS SDS:
 New product.

This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our

knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee, expressed or implied, is made as to its accuracy, reliability, or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license of valid patents.