# SAFETY DATA SHEET



### 1. Identification

**Product identifier** HYDROSTOP PREMIUMCOAT BUTTER GRADE FLASHING

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name **GAF** 

1 Campus Drive

Parsippany, NJ 07054 USA

**Telephone** 1-800-766-3411

**Emergency phone number** CHEMTREC [DAY OR NIGHT] 1-800-424-9300

Within USA and CANADA 1-800-424-9300 Outside USA and Canada: 1703-741-5970

Collect Calls Accepted

2. Hazard(s) identification

Physical hazards Not classified.

**Health hazards** Sensitization, skin Category 1 Category 2

Carcinogenicity

**Environmental hazards OSHA** defined hazards

Not classified. Not classified.

Label elements





Signal word Warning

May cause an allergic skin reaction. May cause cancer. **Hazard statement** 

**Precautionary statement** 

Avoid breathing mist or vapor. Contaminated work clothing must not be allowed out of the Prevention

workplace. Wear protective gloves.

If on skin: Wash with plenty of water. Specific treatment (see this label). If skin irritation or rash Response

occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Store away from incompatible materials. **Storage** 

**Disposal** Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

None known.

## 3. Composition/information on ingredients

### **Mixtures**

SDS 3019

Chemical name	Common name and synonyms	CAS number	%
Calcium Carbonate		1317-65-3	20 to <30
CALCIUM CARBONATE		471-34-1	1 to <5
TITANIUM DIOXIDE		13463-67-7	1 to <5
CARBAMIC ACID, 1H-BENZIMIDAZOL-2-YL, METHYL ESTER		10605-21-7	0.1 to <1

Material name: HYDROSTOP PREMIUMCOAT BUTTER GRADE FLASHING

SDS US Version #: 03 Revision date: 03-23-2020 1/8

Chemical name	Common name and synonyms	CAS number	%
Chloro-2-methyl-4-isothiazolin-3-on e 1.5%		26172-55-4	0.1 to <1
Isobutane		75-28-5	0.1 to <1
Non-Hazardous Ingredients			60 to <70

### 4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop orpersist.

Remove contaminated clothing immediately and wash skin with soap and water. In case of Skin contact

eczema or other skin disorders: Seek medical attention and take along these instructions.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Ingestion

Most important

symptoms/effects, acute and delayed

irritation. May cause an allergic skin reaction. Dermatitis.

Indication of immediate medical attention and special

treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Irritation of eyes and mucous membranes. Rash. Upper respiratory tract irritation. Coughing. Skin

**General information** Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods General fire hazards Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

**Environmental precautions** Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged

exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe

good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

SDS 3019

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

Material name: HYDROSTOP PREMIUMCOAT BUTTER GRADE FLASHING Version #: 03 Revision date: 03-23-2020

# 8. Exposure controls/personal protection

### Occupational exposure limits

Components	Туре	Value	Form
Calcium Carbonate (CAS 1317-65-3)	PEL	5 mg/m3	Respirable fraction
		15 mg/m3	Total dust.
CALCIUM CARBONATE (CAS 471-34-1)	PEL	5 mg/m3	Respirable fraction
		15 mg/m3	Total dust.
TITANIUM DIOXIDE (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
US. ACGIH Threshold Limit	Values		
Components	Туре	Value	
Isobutane (CAS 75-28-5)	STEL	1000 ppm	
TITANIUM DIOXIDE (CAS 13463-67-7)	TWA	10 mg/m3	
US. NIOSH: Pocket Guide to	o Chemical Hazards		
Components	Туре	Value	Form
Calcium Carbonate (CAS 1317-65-3)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
CALCIUM CARBONATE (CAS 471-34-1)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Isobutane (CAS 75-28-5)	TWA	1900 mg/m3	
		800 ppm	
ogical limit values	No higherical exposure limits noted for the	ingredient(s)	

**Biological limit values** 

Appropriate engineering

controls

No biological exposure limits noted for the ingredient(s).

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

#### Individual protection measures, such as personal protective equipment

Skin protection

Hand protection Wear appropriate chemical resistant gloves.Other Wear appropriate chemical resistant clothing.

**Respiratory protection** In case of insufficient ventilation, wear suitable respiratory equipment.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants. Contaminated work clothing should not be allowed out of the

workplace.

## 9. Physical and chemical properties

**Appearance** 

Physical state Liquid. **Form** Liquid. Not available. Color Odor Not available. **Odor threshold** Not available. Not available. pН Melting point/freezing point Not available. Initial boiling point and boiling Not available.

range

SDS 3019

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 0.00001 hPa estimated

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Density8.07 lbs/galPercent volatile30.63 %Specific gravity0.97

**VOC** 10.35 g/l Regulatory estimated

0.06 lbs/gal Material estimated 7.26 g/l Material estimated 0.09 lbs/gal Regulatory estimated

10. Stability and reactivity

**Reactivity** The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Fluorine.

**Hazardous decomposition** 

products

No hazardous decomposition products are known.

# 11. Toxicological information

Information on likely routes of exposure

InhalationProlonged inhalation may be harmful.Skin contactMay cause an allergic skin reaction.

**Eye contact** Direct contact with eyes may cause temporary irritation.

**Ingestion** Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Rash. Irritation of eyes and mucous membranes. Upper respiratory tract irritation. Coughing. Skin

irritation. May cause an allergic skin reaction. Dermatitis.

#### Information on toxicological effects

**Acute toxicity** May cause an allergic skin reaction.

Components Species Test Results

CALCIUM CARBONATE (CAS 471-34-1)

Acute

Oral

LD50 Mouse 6450 mg/kg

Rat 6450 mg/kg

CARBAMIC ACID, 1H-BENZIMIDAZOL-2-YL, METHYL ESTER (CAS 10605-21-7)

Acute

Dermal

LD50 Rabbit > 2000 mg/kg

Rat 2000 mg/kg

Oral

LD50 Dog > 8000 mg/kg

 Guinea pig
 > 5000 mg/kg

 Mouse
 11000 mg/kg

 Rat
 > 5000 mg/kg

Other

LD50 Mouse > 15000 mg/kg

Rat > 2000 mg/kg

Isobutane (CAS 75-28-5)

**Acute** 

Inhalation

LC50 Mouse 52 mg/l, 1 Hours

\* Estimates for product may be based on additional component data not shown.

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not available.

**Skin sensitization** May cause an allergic skin reaction.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Risk of cancer cannot be excluded with prolonged exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

TITANIUM DIOXIDE (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not available.

**Chronic effects** Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

**Ecotoxicity**The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species Test Results

CALCIUM CARBONATE (CAS 471-34-1)

**Aquatic** 

Fish LC50 Western mosquitofish (Gambusia affinis) > 56000 mg/l, 96 hours

CARBAMIC ACID, 1H-BENZIMIDAZOL-2-YL, METHYL ESTER (CAS 10605-21-7)

**Aquatic** 

Fish LC50 Channel catfish (Ictalurus punctatus) 0.009 - 0.015 mg/l, 96 hours

TITANIUM DIOXIDE (CAS 13463-67-7)

Aquatic

Crustacea EC50 Water flea (Daphnia magna) > 1000 mg/l, 48 hours
Fish LC50 Mummichog (Fundulus heteroclitus) > 1000 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

CARBAMIC ACID, 1H-BENZIMIDAZOL-2-YL, METHYL 1.52

**ESTER** 

Isobutane 2.76

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

# 13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

US RCRA Hazardous Waste U List: Reference

CARBAMIC ACID, 1H-BENZIMIDAZOL-2-YL, METHYL U372

ESTER (CAS 10605-21-7)

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

## 14. Transport information

DOT

Not regulated as dangerous goods.

**IATA** 

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

This substance/mixture is not intended to be transported in bulk.

the IBC Code

## 15. Regulatory information

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

#### **US federal regulations**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910,1200.

All Components are on the U.S. EPA TSCA Inventory List

### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Chloro-2-methyl-4-isothiazolin-3-one 1.5% (CAS

26172-55-4) Listed.

### CERCLA Hazardous Substance List (40 CFR 302.4)

CARBAMIC ACID, 1H-BENZIMIDAZOL-2-YL, METHYL ESTER (CAS 10605-21-7)

Isobutane (CAS 75-28-5)

Listed.

### SARA 304 Emergency release notification

Not regulated.

## OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

## SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

### SARA 313 (TRI reporting)

Not regulated.

#### Other federal regulations

### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

## Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Isobutane (CAS 75-28-5)

Safe Drinking Water Act

Not regulated.

(SDWA)

#### **US** state regulations

### US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

### **US. Massachusetts RTK - Substance List**

Calcium Carbonate (CAS 1317-65-3)

CALCIUM CARBONATE (CAS 471-34-1)

Isobutane (CAS 75-28-5)

TITANIUM DIOXIDE (CAS 13463-67-7)

# US. New Jersey Worker and Community Right-to-Know Act

Calcium Carbonate (CAS 1317-65-3)

CALCIUM CARBONATE (CAS 471-34-1)

CARBAMIC ACID, 1H-BENZIMIDAZOL-2-YL, METHYL ESTER (CAS 10605-21-7)

Isobutane (CAS 75-28-5)

TITANIUM DIOXIDE (CAS 13463-67-7)

## US. Pennsylvania Worker and Community Right-to-Know Law

Calcium Carbonate (CAS 1317-65-3)

CALCIUM CARBONATE (CAS 471-34-1)

Isobutane (CAS 75-28-5)

TITANIUM DIOXIDE (CAS 13463-67-7)

### **US. Rhode Island RTK**

CARBAMIC ACID, 1H-BENZIMIDAZOL-2-YL, METHYL ESTER (CAS 10605-21-7) Isobutane (CAS 75-28-5)

# **US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer.

# US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

3-(3,4 Dichlorophenyl)-1,1-Dimethylurea(CAS Listed: May 31, 2002

330-54-1)

TITANIUM DIOXIDE (CAS 13463-67-7) Listed: September 2, 2011

Material name: HYDROSTOP PREMIUMCOAT BUTTER GRADE FLASHING

Version #: 03 Revision date: 03-23-2020

SDS US

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No

Europe European List of Notified Chemical Substances (ELINCS) No
Japan Inventory of Existing and New Chemical Substances (ENCS) No
Korea Existing Chemicals List (ECL) No
New Zealand New Zealand Inventory No
Philippines Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

## 16. Other information, including date of preparation or last revision

 Issue date
 10-01-2014

 Revision date
 03-23-2020

Version # 03

HMIS® ratings Health: 2

Flammability: 0 Physical hazard: 0 Personal protection: D

NFPA ratings Health: 2

Flammability: 0 Instability: 0

Disclaimer

This information relates to the specific material designated and may not be valid for such material used on combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, **no representation**, **warranty or guarantee**, expressed or implied, **is made** as to its accuracy, reliability, or completeness. GAF cannot anticipate all conditions under which this information and product, or the products of other manufacturers in combination with this product, may be used. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his particular use. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. **We do not accept liability** for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license of valid patents.

Material name: HYDROSTOP PREMIUMCOAT BUTTER GRADE FLASHING Version #: 03 Revision date: 03-23-2020

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).