



**GAF**  
**Safety Data Sheet**  
**SDS # 4060**  
**SDS Date: July 2021**

## 1. IDENTIFICATION

**PRODUCT NAME:** Premium Acrylic HydroStop Top Coat

**MANUFACTURER:** GAF

**ADDRESS:** 1 Campus Drive, Parsippany, NJ 07054

**24-HOUR EMERGENCY  
PHONE (CHEMTREC):** 800 – 424 – 9300

**INFORMATION ONLY:** 800 – 766 – 3411

**PREPARED BY:** Corporate EHS

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

### Label elements

#### **GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)**

|                           |            |
|---------------------------|------------|
| Skin Corrosion/Irritation | Category 3 |
| Carcinogenicity Category  | Category 2 |

### **Pictogram:**



**Signal word:** Warning

#### **Hazard statement(s)**

Suspected of causing cancer.  
Causes mild skin irritation.

#### **Precautionary Statements - Prevention**

Wear protective gloves.  
Wear eye or face protection.  
Use only outdoors or in a well-ventilated area.

Avoid breathing vapor.  
Wash hands thoroughly after handling.  
Contaminated work clothing should not be allowed out of the workplace.

**IF INHALED:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.

**IF ON SKIN:** Wash with plenty of soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention.

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

**Hazards not otherwise classified (HNOC)**

Not applicable.

**Other Information**

Unknown acute toxicity.

**ADDITIONAL HAZARD IDENTIFICATION INFORMATION:**

**PRIMARY ROUTE OF EXPOSURE:** Skin Contact

**SIGNS & SYMPTOMS OF EXPOSURE**

**EYES:** Direct contact with eyes may cause temporary irritation.

**SKIN:** Prolonged skin contact may cause temporary irritation.

**INGESTION:** Not expected to be ingested.

**INHALATION:** May cause irritation.

**ACUTE HEALTH HAZARDS:** Skin irritation.

**CHRONIC HEALTH HAZARDS:** None known

**CARCINOGENICITY:** IARC has determined that occupational exposure to Titanium Dioxide is possibly carcinogenic to humans (Group 2B).

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Substance**

| Chemical Name             | CAS No.    | Weight-% |
|---------------------------|------------|----------|
| Calcium Carbonate         | 1317-65-3  | 30 – 40  |
| Titanium Dioxide          | 13463-67-7 | 5 - 10   |
| Zinc Oxide                | 1314-13-2  | 1 – 5    |
| Non-hazardous ingredients | -          | 50 – 60  |

#### 4. FIRST AID MEASURES

##### Description of first aid measures

|                     |  |
|---------------------|--|
| <b>Eye contact</b>  | Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.  |
| <b>Skin contact</b> | Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.  |
| <b>Inhalation</b>   | Remove victim to fresh air and keep at rest in a position comfortable for breathing. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway.   |
| <b>Ingestion</b>    | Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Get medical attention immediately. |

**Most important symptoms and effects, both acute and delayed** Slight irritation of eyes and skin.

**Indication of any immediate medical attention and special treatment needed** Provide general supportive measures and treat symptomatically. Keep the victim under observation. Symptoms may be delayed.

**Note to physicians** Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested.

#### 5. FIRE-FIGHTING MEASURES

##### Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment including water fog, dry chemical powder, carbon dioxide.

**Unsuitable extinguishing media** None known.

**Specific hazards arising from the chemical** No information available.

**Explosion data** In a fire or if heated, a pressure increase will occur and the container may burst.

**Sensitivity to Static Discharge** None.

##### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Isolate materials not yet involved in the fire and protect personnel. Move containers from the fire area if this can be done without risk; otherwise, cool with carefully applied water spray. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas.

#### 6. ACCIDENTAL RELEASE MEASURES

##### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. For personal protection see section 8.

##### Environmental precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

**Methods and material for containment and cleaning up**

**Methods for containment** Contain spill if safe to do so. Prevent entry into drains, sewers, and other waterways. Soak up with a non-combustible absorbent material and place in an appropriate container for disposal. Dispose of in accordance with applicable Federal, State, and local procedures (see section 13).

**Methods for cleaning up** Stop leak if without risk. Move containers from the spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in a container for disposal according to local regulations (see section 13 of SDS). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

## 7. HANDLING AND STORAGE

**Precautions for safe handling**

**Advice on safe handling** Handle in accordance with good industrial hygiene and safety practice. For exterior use only. Do not use indoors. Put on appropriate personal protective equipment (see section 8 of SDS). Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse containers.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10 of SDS) and food and drink. Store locked up. Keep the container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers

**Incompatible materials** None known based on information supplied.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters**

**Occupational Exposure Limits:**

**Control parameters**

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR1910.1000)**

**Calcium Carbonate (CAS 1317-65-3)**

PEL 5 mg/m<sup>3</sup> Respirable fraction.  
15 mg/m<sup>3</sup> Total dust.

**Titanium Dioxide (CAS 13463-67-7)**

PEL 15 mg/m<sup>3</sup> Total dust.

**US. ACGIH Threshold Limit Values**

**Titanium Dioxide (CAS 13463-67-7)**TLV 10 mg/m<sup>3</sup> Respirable fraction.**Zinc Oxide (CAS 1314-13-2)**TLV 10 mg/m<sup>3</sup> Respirable fraction.**Appropriate engineering controls**

**Engineering Controls**

- Showers
- Eyewash stations
- Adequate ventilation

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Safety glasses or chemical goggles as appropriate to prevent eye contact.

**Skin and body protection** Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. Personal protective equipment for the body should be selected based on the task being performed and the risks involved

**Respiratory protection** If exposure limits are exceeded or irritation is experienced, a NIOSH/MSHA approved respiratory protection should be worn.

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice.

**9. PHYSICAL AND CHEMICAL PROPERTIES****Information on basic physical and chemical properties**

**Physical state and color** White heavy liquid

| <b><u>Property</u></b>           | <b><u>Values</u></b>     |
|----------------------------------|--------------------------|
| pH                               | No information available |
| Melting point/freezing point     | No information available |
| Boiling point / boiling range    | > 100 deg C > 212 deg F  |
| Flash point                      | > 100 deg C > 212 deg F  |
| Evaporation rate                 | No information available |
| Flammability (solid, gas)        | Non-Flammable            |
| <b>Flammability Limit in Air</b> |                          |
| Upper flammability limit:        | Non-Flammable            |
| Lower flammability limit:        | Non-Flammable            |
| Vapor pressure                   | No information available |
| Vapor density                    | No information available |
| Specific Gravity                 | 1.42                     |
| Water solubility                 | No information available |
| Autoignition temperature         | No information available |
| Decomposition temperature        | No information available |
| Explosive properties             | No information available |
| Oxidizing properties             | No information available |
| VOC Content                      | < 50 g/L                 |
| Density                          | 11.8 lbs/gal             |

**10. STABILITY AND REACTIVITY****Reactivity**

The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of Hazardous Reactions**

None under normal processing.

**Conditions to avoid**

Extremes of temperature and contact with incompatible chemicals.

**Incompatible materials**

Amines, mercaptans and Lewis acids at ambient temperature and above. Strong acids and oxidizing agents Strong alkalis.

**Hazardous Decomposition Products**

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

**11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

|                     |  |
|---------------------|--|
| <b>Inhalation</b>   | Prolonged inhalation may be harmful.                     |
| <b>Eye contact</b>  | Direct contact with eyes may cause temporary irritation. |
| <b>Skin contact</b> | May cause slight skin irritation.                        |
| <b>Ingestion</b>    | Expected to be a low ingestion hazard.                   |

**Zinc Oxide (CAS 1314-13-2)**

Acute Inhalation

LC50 Mouse > 5.7 mg/l, 4 Hours

Oral LD50 Mouse 7950 mg/kg

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

|                                 |   |
|---------------------------------|---|
| <b>Sensitization</b>            | No information available.   |
| <b>Germ cell mutagenicity</b>   | No information available.   |
| <b>Carcinogenicity</b>          | IARC has determined that occupational exposure to Titanium Dioxide is possibly carcinogenic to humans (Group 2B). |
| <b>Reproductive toxicity</b>    | No information available.   |
| <b>STOT - single exposure</b>   | No information available.   |
| <b>STOT - repeated exposure</b> | No information available.   |
| <b>Aspiration hazard</b>        | No information available.   |

**Potential acute health effects**

|                       |                                |
|-----------------------|--------------------------------|
| <b>Eye contact :</b>  | May cause mild eye irritation. |
| <b>Inhalation :</b>   | None known.                    |
| <b>Skin contact :</b> | Causes mild skin irritation.   |
| <b>Ingestion :</b>    | None known.                    |

**12. ECOLOGICAL INFORMATION****Ecotoxicity**

100 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

**Titanium Dioxide (CAS 13463-67-7)**

Aquatic

EC50 Water flea (Daphnia magna) Mummichog (Fundulus heteroclitus) > 1000 mg/l, 48 hours

LC50 Fish Fathead minnow (*Pimephales promelas*)

> 1000 mg/l, 96 hours

**Zinc Oxide (CAS 1314-13-2)**

Aquatic

LC50 Crustacea Fish

2246 mg/l, 96 hours

**Persistence and degradability**

Not readily biodegradable

**Bioaccumulation**

No information available.

**Other adverse effects**

No known significant or critical hazards.

## 13. DISPOSAL CONSIDERATIONS

**Waste treatment methods**

**Disposal of wastes**

Disposal should be in accordance with applicable local, regional, national and international laws and regulations.

**Contaminated packaging**

Do not reuse containers.

## 14. TRANSPORT INFORMATION

**DOT**

Not regulated.

**IATA**

Not regulated.

**IMDG**

Not regulated.

## 15. REGULATORY INFORMATION

**US Federal Regulations**

**TSCA**

This product and its components are listed on the TSCA 8(b) inventory.

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

**SARA 311/312 Hazard Categories**

|                                   |     |
|-----------------------------------|-----|
| Acute health hazard               | Yes |
| Chronic Health Hazard             | No  |
| Fire hazard                       | No  |
| Sudden release of pressure hazard | No  |
| Reactive Hazard                   | No  |

**CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

**CERCLA**

Pure (Dibutyl Phthalate)

**US State Regulations**

Other state regulations may apply. Check individual state requirements. The following components appear on one or more of the following state hazardous substances lists:

| Chemical Name            | CAS #      | CA  | MA  | MN  | NJ  | PA  | RI  |
|--------------------------|------------|-----|-----|-----|-----|-----|-----|
| Pure (Dibutyl Phthalate) | 84-74-2    | Yes | Yes | Yes | Yes | Yes | Yes |
| Zinc Oxide               | 1314-13-2  | Yes | No  | Yes | Yes | Yes | Yes |
| Titanium Dioxide         | 13463-67-7 | No  | No  | Yes | Yes | Yes | Yes |

**California Proposition 65**

Pure (Dibutyl Phthalate), and titanium dioxide are California Proposition 65 listed substances.

**16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION**

|             |                  |                |                    |                                    |
|-------------|------------------|----------------|--------------------|------------------------------------|
| <b>NEPA</b> | Health hazards 1 | Flammability 0 | Instability 0      | Physical and Chemical Properties - |
| <b>HMIS</b> | Health hazards 1 | Flammability 0 | Physical hazards 0 | Personal protection X              |

**ADDITIONAL COMMENTS:** None.

**DATE OF PREVIOUS SDS:** None. New SDS.

**CHANGES SINCE PREVIOUS SDS:** New SDS.

This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee, expressed or implied, is made as to its accuracy, reliability, or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license of valid patents.