

GAF Safety Data Sheet SDS # 1006

SDS Date: April 2018

SECTION 1: PRODUCT AND COMPANY INFORMATION

PRODUCT NAME: Ruberoid® 30 Granule

Ruberoid® 30 Granule FR

Ruberoid® 30 Granule FR EnergyCap®

TRADE NAME: Roll Roofing

MANUFACTURER: GAF

ADDRESS: 1 Campus Drive, Parisppany, NJ 07054

24-HOUR EMERGENCY PHONE

(CHEMTREC):

800 - 424 - 9300

INFORMATION ONLY: 800 – 766 – 3411

PREPARED BY: Corporate EHS

APPROVED BY: Corporate EHS

SECTION 2: HAZARDS IDENTIFICATION

As defined in the OSHA Hazard Communication Standard, 29 CFR 1910.1200, the products listed below are considered articles and do not require an SDS. In addition, articles are not included in the scope of the Globally Harmonization System (GHS). As such, the GHS labeling elements are not included on this SDS. All components listed for this product are bound within the product. When handled as intended and under normal conditions of use, there is no evidence that any of the ingredients are released in amounts that pose a significant health risk. Although these products are not subject to the OSHA Standard or GHS labeling elements, GAF would like to disclose as much health and safety information as possible to ensure that this product is handled and used properly. This SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and be made available for employees and other users of this product. In addition, the recommendations for handling and use of these products should be included in worker training programs.

ADDITIONAL HAZARD IDENTIFICATION INFORMATION:

PRIMARY ROUTE OF EXPOSURE: Occasional nuisance dust, Inhalation

SIGNS & SYMPTOMS OF EXPOSURE

EYES: May cause irritation to the eyes.

SKIN: May cause irritation to the skin.

INGESTION: Not applicable.

INHALATION: May cause irritation to the respiratory tract.

ACUTE HEALTH HAZARDS: NIOSH has found that studies of workers exposed to asphalt

fumes have repeatedly found irritation of the serous membranes of the conjunctivae (eye irritation) and the mucous membranes of the

upper respiratory tract (nasal and throat irritation).

CHRONIC HEALTH HAZARDS: Studies in humans have found that exposure to respirable

crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs. Silicosis is a serious and irreversible disease; it may be progressive even after exposure has ceased; it can lead to disability and death. Human studies also have found that silicosis is a risk factor for tuberculosis, and that occupational exposure to respirable crystalline silica is associated with chronic obstructive pulmonary disease, including bronchitis and emphysema. Some studies show excess numbers of cases of scleroderma, connective tissue disorders, lupus, rheumatoid arthritis, chronic kidney diseases and end-stage kidney disease in workers exposed to

respirable crystalline silica.

CARCINOGENICITY: Crystalline Silica: The International Agency for Research on

Cancer (IARC) Group 1 - Known Human Carcinogen (listed under Crystalline silica inhaled in the form of quartz or cristobalite from

occupational sources).

IARC has determined that occupational exposure to oxidized asphalt and its emissions is probably carcinogenic to humans

(Group 2A).

IARC has determined that occupational exposure to Titanium Dioxide is possibly carcinogenic to humans (Group 2B).

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

			OCCUPATIONAL EXPOSURE LIMITS			
CHEMICAL NAME	CAS#	% (BY WT)	OSHA	ACGIH	OTHER	
Oxidized Asphalt	64742-93-4	40-45	NE	0.5 mg/m3 (inhalable fraction, as benzene-soluble aerosol)	5 mg/m3 – ceiling (15 min. fumes)	
Granules	-	~30	NE	NE	NE	
Limestone	1317-65-3	~15	5 mg/m3 resp. 15 mg/m3 total	3 mg/m3 resp. 10 mg/m3 total	REL: 5 mg/m3 resp. 15 mg/m3 total	
Titanium Dioxide	13463-67-7	0 – 4	15 mg/m3 total	10 mg/m3 total		
Silica, Crystalline Quartz	14808-60-7	0.1-1	50 ug/m3 / (% SiO2 + 2) – resp.	0.025 mg/m3	REL: 0.05 mg/m3 – resp.	

NE = Not Established

SECTION 4: FIRST AID MEASURES

FIRST AID PROCEDURES

EYES: Hold eyelids open and wash with gentle stream of water for at least 15

minutes preferably at eyewash fountain.

SKIN: Wash exposed skin with soap and water. If irritation develops or persists,

seek medical attention.

INHALATION: More individual to area with fresh air and provide oxygen if breathing is

difficult. Consult medical personnel.

INGESTION: Consult medical personnel.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:

Dust from the product may cause mechanical irritation of the eyes, skin,

and upper respiratory tract. Treat symptomatically.

SECTION 5: FIRE FIGHTING PROCEDURES

SUITABLE EXTINGUISHING MEDIA: Water spray, Alcohol foam, Carbon Dioxide, or Dry chemical.

HAZARDOUS COMBUSTION PRODUCTS: Carbon dioxide and carbon monoxide.

RECOMMENDED FIRE FIGHTING

PROCEDURES:

NIOSH-approved self contained breathing apparatus is

recommended for smoke protection.

UNUSUAL FIRE & EXPLOSION

HAZARDS:

None.

SECTION 6: ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES: Pick up pieces and dispose off properly. Vacuum dust. Use a dust

suppressant if sweeping is necessary.

SECTION 7: HANDLING AND STORAGE

HANDLING AND STORAGE: Hot asphalt is used to apply many of these products; appropriate

personal protective equipment should be worn handling this

material.

OTHER PRECAUTIONS: When heated, small amounts of hydrogen sulfide may be given

off. Hydrogen sulfide is a flammable, toxic gas. Avoid breathing fumes.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS /

VENTILATION:

Not Applicable.

RESPIRATORY PROTECTION: Not applicable under normal use conditions. In circumstances

where dust or fumes are generated and may exceed recognized allowable exposure levels, appropriate NIOSH approved respiratory

protection is recommended.

EYE PROTECTION: Safety glasses with side shields

SKIN PROTECTION: Cotton or leather gloves are recommended when handling.

OTHER PROTECTIVE EQUIPMENT: Work shoes.

Wash exposed skin prior to eating, drinking or smoking and at the

WORK HYGIENIC PRACTICES: end of each shift.

These products should be handled using methods and techniques

EXPOSURE GUIDELINES: that minimize or eliminate dust or fume generation.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE & ODOR:	Thin black sheet in roll form, may be surfaced with granules, talc, sand or film. Slight asphalt odor.					
FLASH POINT:	>500° F	LOWER EXPLOSIVE LIMIT:	No Data			
METHOD USED:	COC	UPPER EXPLOSIVE LIMIT:	No Data			
EVAPORATION RATE:	No Data	BOILING POINT:	No Data			
pH (undiluted product):	No Data	MELTING POINT:	No Data			
SOLUBILITY IN WATER:	No Data	SPECIFIC GRAVITY:	No Data			
VAPOR DENSITY:	No Data	PERCENT VOLATILE:	No Data			
VAPOR PRESSURE:	No Data	MOLECULAR WEIGHT:	No Data			
VOC WITH WATER (LBS/GAL):	No Data	WITHOUT WATER (LBS/GAL):	No Data			

GAF SDS # 1006 SECTION 10: STABILITY AND REACTIVITY THERMAL STABILITY: STABLE X UNSTABLE **CONDITIONS TO AVOID (STABILITY):** None known. **INCOMPATIBILITY (MATERIAL TO** None known. AVOID): HAZARDOUS DECOMPOSITION OR BY-None known. PRODUCTS: **HAZARDOUS POLYMERIZATION:** Will Not Occur **SECTION 11: TOXICOLOGICAL INFORMATION** TOXICOLOGICAL INFORMATION: Crystalline silica is considered a hazard by inhalation. The International Agency for Research on Cancer (IARC) has classified crystalline silica as a Group 1 substance, carcinogenic to humans. This classification is based on the findings of laboratory animal studies (inhalation and implantation) and epidemiology studies that were considered sufficient for carcinogenicity. Excessive exposure to crystalline silica can cause silicosis, a noncancerous lung disease. IARC has determined that occupational exposure to oxidized asphalt and its emissions is probably carcinogenic to humans (Group 2A). IARC has determined that occupational exposure to Titanium Dioxide is possibly carcinogenic to humans (Group 2B). **SECTION 12: ECOLOGICAL INFORMATION ECOLOGICAL INFORMATION:** No information available **SECTION 13: DISPOSAL CONSIDERATIONS**

WASTE DISPOSAL METHOD: Dispose of waste material according to Local, State, and Federal,

environmental regulations.

SECTION 14: TRANSPORTATION INFORMATION

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS

TSCA: This product and its components are listed on the TSCA 8(b)

inventory.

CERCLA: None

SARA

311/312 HAZARD CATEGORIES: None

313 REPORTABLE INGREDIENTS: None

CALIFORNIA PROPOSITION 65: This product contains silica and titanium dioxide, chemicals known

to the State of California to cause cancer.

Other state regulations may apply. Check individual state requirements. The following components appear on one or more of the following state hazardous substances lists:

Chemical Name	CAS#	CA	MA	MN	NJ	PA	RI
Oxidized Asphalt	64742-93-4	No	No	No	No	No	No
Crystalline Silica	14808-60-7	Yes	Yes	Yes	Yes	Yes	Yes
Titanium Dioxide	13463-67-7	No	Yes	Yes	Yes	Yes	Yes
Limestone	1317-65-3	No	Yes	Yes	No	Yes	Yes

SECTION 16: OTHER INFORMATION

ADDITIONAL COMMENTS: None

DATE OF PREVIOUS SDS: October 2016

CHANGES SINCE PREVIOUS SDS: Product Name Change

This information relates to the specific material designated and may not be valid for such material used on combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation,

warranty or guarantee, expressed or implied, is made as to its accuracy, reliability, or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license of valid patents.