



GAF
Safety Data Sheet
SDS # 3046
SDS Date: July 2022

SECTION 1: PRODUCT AND COMPANY INFORMATION

PRODUCT NAME: Surface Seal SB Roof Coating

MANUFACTURER: GAF

ADDRESS: 1 Campus Drive, Parsippany, NJ 07054

**24-HOUR EMERGENCY
PHONE (CHEMTREC):** 800 – 424 – 9300

INFORMATION ONLY: 877-GAF-ROOF

PREPARED BY: Corporate EHS

SECTION 2: HAZARDS IDENTIFICATION

NFPA and HMIS RATINGS:

	NFPA Hazard Rating		HMIS Hazard Rating
Health	3	Health	3
Flammable	3	Flammable	3
Reactive	0	Reactive	0
Special Hazards	-	Personal Protection	X

GHS LABEL ELEMENTS:

**GHS
CLASSIFICATION:** Flammable Liquid - Category 3
Eye Irritant - Category 2A
Skin Irritant - Category 2
Aspiration Toxicity - Category 1
Target Organ (SE) - Category 3
Target Organ (RE) - Category 2
Reproductive Toxicity - Category 2
Hazardous to the Aquatic Environment (chronic) -
Category 3

GHS PICTOGRAMS:



SIGNAL WORD: Danger

HAZARD STATEMENTS: Flammable liquid and vapor.
May cause damage to organs through prolonged or repeated exposure.
May cause respiratory irritation.
May cause cancer.
May cause genetic defects.
Causes skin irritation.
Harmful if inhaled.
Causes serious eye irritation.
May be fatal if swallowed or enters airways.
May cause drowsiness or dizziness.
Suspected of damaging fertility or the unborn child
Harmful to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ ventilating/ lighting/ equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
Wash skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/ eye protection/ face protection.
Get medical advice/ attention if you feel unwell.
Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
In case of fire: Use carbon dioxide (CO₂), foam, dry extinguishing powder to extinguish.
Dispose of contents/container to a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous waste.
Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER or physician if you feel unwell.
IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

ADDITIONAL HAZARD IDENTIFICATION INFORMATION:

PRIMARY ROUTE OF EXPOSURE: Eye contact, Skin contact, Inhalation

SIGNS & SYMPTOMS OF EXPOSURE

EYES: This material causes eye irritation. Contact with the liquid or exposure to mist or vapor may cause stinging, redness and swelling.

SKIN: This material may cause mild skin irritation. Prolonged contact may cause redness, burning and drying or cracking of the skin.

INGESTION: Harmful or fatal if swallowed and/or vomiting occurs. Can enter lungs and cause damage. This material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

INHALATION: High concentrations of vapor or mist may cause irritation of the nose and throat and signs of nervous system depression. Can cause headaches, drowsiness, dizziness, and loss of coordination.

ACUTE HEALTH HAZARDS: See above.

CHRONIC HEALTH HAZARDS: None known.

CARCINOGENICITY: IARC has determined that occupational exposure to Titanium Dioxide is possibly carcinogenic to humans (Group 2B).

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL NAME	CAS #	% (BY WT)	OCCUPATIONAL EXPOSURE LIMITS		
			OSHA	ACGIH	OTHER
solvent naphtha (petroleum), light aromatic	64742-95-6	30 – 40	NE	NE	NE
Aluminum hydroxide	21645-51-2	20 – 30	500 ppm	100 ppm	NE
Titanium Dioxide	13463-67-7	10 – 15	NE	NE	NE

Balance of other ingredients are non-hazardous or less than 1% in concentration (or 0.1% for carcinogens, reproductive toxins, or respiratory sensitizers).

NE = Not Established

SECTION 4: FIRST AID MEASURES

FIRST AID PROCEDURES

EYES: Flush eyes immediately with water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician.

SKIN:	Remove contaminated clothes. Wash exposed areas with soap and water. If redness or swelling develops, seek medical assistance. Wash clothing separately before reuse. Destroy or thoroughly clean contaminated shoes.
INHALATION:	Remove to fresh air. If breathing has stopped, give artificial respiration. Call a physician.
INGESTION:	Rinse mouth thoroughly. Do not induce vomiting without advice from poison control center. Do not give mouth-to-mouth resuscitation. If vomiting occurs, keep head low so that stomach content does not get into the lungs. Never give anything by mouth to a victim who is unconscious or is having convulsions. Get medical attention immediately.
NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:	Symptoms may be delayed.

SECTION 5: FIRE FIGHTING PROCEDURES

SUITABLE EXTINGUISHING MEDIA:	Water spray, water fog, CO ₂ , dry chemical powder, sand and foam.
HAZARDOUS COMBUSTION PRODUCTS:	Carbon dioxide and carbon monoxide.
RECOMMENDED FIRE FIGHTING PROCEDURES:	Self contained breathing apparatus recommended. Use water spray to cool unopened containers.
UNUSUAL FIRE & EXPLOSION HAZARDS:	Material is flammable and may be ignited by flames, sparks, heat or other sources of ignition. Do not use a solid water stream as it may scatter and spread fire. Vapor may cause flash fire. Vapors can flow along surfaces to distant ignition source and flash back. Sensitive to static discharge. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

SECTION 6: ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES:	Eliminate all ignition sources (no smoking, flares, sparks or flames in the immediate area). Extinguish all flames in the vicinity. Dam up area to prevent spreading of material. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Cover with plastic sheet to prevent spreading. Collect spillage. Prevent product from entering drains. Do not allow material to contaminate groundwater system.
-------------------------------------	--

SECTION 7: HANDLING AND STORAGE

HANDLING AND STORAGE:	Store in a well ventilated area, 50 – 80°F. Ensure good ventilation of the work station. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Obtain special
------------------------------	--

instructions before use. Do not handle until all safety precautions have been read and understood. Eliminate all ignition sources if safe to do so. Do not breathe fume, spray, or vapor. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Wear personal protective equipment. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly.

OTHER PRECAUTIONS:

The container is hazardous when empty. Partially full or emptied container may contain explosive vapors. Do not cut, weld, or solder on/or near the container. Do not reuse "empty" container without commercial cleaning or reconditioning

Do not eat, drink or smoke when using this product. Do not eat, drink or smoke when using this product, Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work thoroughly after handling. Separate working clothes from town clothes. Launder separately. Always wash hands after handling the product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**ENGINEERING CONTROLS /
VENTILATION:**

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure limits.

RESPIRATORY PROTECTION:

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

EYE PROTECTION:

Safety goggles or safety glasses with side shields.

SKIN PROTECTION:

Wear appropriate impermeable gloves and protective clothing as necessary to prevent skin contact.

OTHER PROTECTIVE EQUIPMENT:

None.

WORK HYGIENIC PRACTICES:

Wash exposed skin prior to eating, drinking, or smoking and at the end of each shift.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**APPEARANCE & ODOR:**

Gray liquid with a solvent odor (may be colored).

FLASH POINT:	105 °F	LOWER EXPLOSIVE LIMIT:	0.5%
METHOD USED:	TCC	UPPER EXPLOSIVE LIMIT:	6.0%
EVAPORATION RATE:	0.37	BOILING POINT:	310-355 °F
pH (undiluted product):	No data	MELTING POINT:	No data
SOLUBILITY IN WATER:	Insoluble	SPECIFIC GRAVITY:	1.21
VAPOR DENSITY:	4.2	PERCENT VOLATILE:	No data
VAPOR PRESSURE:	2.9 kPa	MOLECULAR WEIGHT:	No data
VOC (g/L):	<550		

SECTION 10: STABILITY AND REACTIVITY

THERMAL STABILITY:

STABLE X

UNSTABLE ☐

CONDITIONS TO AVOID:

Heat, flames and sparks. Ignition sources. Contact with incompatible materials. Do not pressurize, cut, weld, braze, solder, drill, grind or expose empty containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode and cause injury or death.

INCOMPATIBILITY (MATERIAL TO AVOID):

Strong oxidizing agents.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:

Carbon dioxide or carbon monoxide.

HAZARDOUS POLYMERIZATION:

Will not occur.

SECTION 11: TOXICOLOGICAL INFORMATIONEye contact: Causes eye irritation.Inhalation: May cause respiratory irritation.Ingestion: Harmful or fatal if swallowed and enters airways.Skin contact: May cause moderate irritation.Teratogenicity: No known significant effects or critical hazards.Germ cell mutagenicity: May cause genetic defects (Dermal, Inhalation).Carcinogenicity: May cause cancer.

Titanium Dioxide - IARC 2B Possibly carcinogenic to humans,

Specific target organ toxicity (repeated exposure): Causes damage to organs (central nervous system, eye, Skin, lung, liver) through prolonged or repeated exposure (Dermal, Inhalation).

SECTION 12: ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION:**Solvent Naphtha**

ECOTOXICITY Material -- Expected to be toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

Log Pow 2.1 - 6

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose in accordance with all applicable local, state and Federal regulations. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container.

SECTION 14: TRANSPORTATION INFORMATION

DOT

Not regulated (if shipped in NON BULK packaging by ground transport) per DOT Exemption Combustible Liquid 173.150(1)(f)

IATA

UN number	UN1993
UN proper shipping name	Flammable liquid n.o.s. (Light aromatic petroleum naphtha)
Hazard Air Class	3
Packing group	III

IMDG

UN Number	UN1993
UN proper shipping name	Flammable liquid n.o.s. (Light aromatic petroleum naphtha)
Hazard Class	3
Packing group	III
EmS-No	F-E, S-E

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS

TSCA: This product and its components are listed on the TSCA 8(b) inventory.

CERCLA: Not applicable.

SARA

311/312 HAZARD CATEGORIES: Acute Health Hazard, Chronic Health Hazard, Fire Hazard

313 REPORTABLE INGREDIENTS: Not applicable.

CALIFORNIA PROPOSITION 65: Cancer: Titanium dioxide.

SECTION 16: OTHER INFORMATION

ADDITIONAL COMMENTS: None

DATE OF PREVIOUS SDS: February 2019

CHANGES SINCE PREVIOUS SDS: Name change.

This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee, expressed or implied, is made as to its accuracy, reliability, or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license of valid patents.